#### **DOE Zero Energy Ready Home**





Zero Energy Ready Home Training

**SAM RASHKIN** 

Chief Architect
Building Technologies Office

#### AIA LU's



Credit(s) earned on completion of this course will be reported to AIA CES for AIA members.

Certificates of Completion for both AIA members and non-AIA members are available upon request.

CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.

Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.

This course is registered with AIA



#### Course Description



DOE Zero Energy Ready Home training sessions provide dynamic content on the business case and technical strategies to successfully design and build zero energy ready homes in today's market. The training features multiple modules covering the business advantages of high performance building, marketing to consumers, advanced building specifications and systems, and gaining recognition through DOE Zero Energy Ready Home Home.



#### Learning Objectives



- Understand the business case for constructing zero energy ready homes.
- 2. Recognize the home buyer value propositions for purchasing zero netenergy homes.
- 3. Understand the DOE technical specifications associated with zero energy ready performance.
- 4. Understand how to gain recognition for construction zero energy ready homes with the DOE Zero Energy Ready Home program



#### For More Information





#### Web Site:

www.buildings.energy.gov/zero/

e-mail Contact:

zero@newportpartnersllc.com

### Agenda: Morning





#### Zero Business Solution:

- Zero Building Blocks
- Zero Common Agenda
- Zero for Informed Buyers
- Zero Value Translated

#### Zero Builders in Action

- Name 1
- Name 2

#### Agenda: Afternoon





## Zero Specifications

- Optimized Enclosure System
- Water Protection Systems
- Optimized Comfort System
- Comprehensive IAQ System
- Efficient Component System
- Solar Ready System
- Summary

# Zero Recognition

- Zero Energy Ready Home Resources
- Partnering with Zero Energy Ready Home
- Meet the Raters: Local Solution



# Zero Energy Ready Home Training Zero Building Blocks

## Welcome to New Risk Reality






Image Basis: Building Energy Codes Program: National Benefits Assessment, 1992-2040, https://www.energycodes.gov/sites/default/files/documents/BenefitsReport\_Final\_March20142.pdf



#### Risk Driver:

Advanced Enclosure

# Outcome:

- + Insulation
- + Windows
- + Air Sealing

#### Reality:

- > Code Rigor
- < HERS Index

#### Building Block #1: Whole-House Water Protection





**Risk Driver:** 


Advanced **Enclosure** 

Outcome:

**Colder Surfaces Less Drying** 

Moisture Risk:

More Wetting **Potential** 



#### **HVAC QI:**

Right-Sizing Var. Speed

Ducts in Cond. Space

Proper Installation

Complete

#### **Comfort Risk:**

< Mixing

< RH Control

#### **Risk Driver:**

Advanced Enclosure


#### Outcome:

< Loads, > MRT Control

< Air Flow, > Swing Season

# Building Block #3: Comprehensive Indoor Air Quality





#### **IAQ System:**

Source Control

Fresh Air System

High-Capture Filtration

#### Risk Driver:

Advanced Enclosure

#### Outcome:


Less
Air Exchange

#### IAQ Risk:

More Contaminants

# Building Block #4: Optimized Enclosure





#### **Future Code:**

- + Air Tight
- + Window Eff.
  - + Insulation

#### **Risk Driver:**

Optimized Enclosure

#### Outcome:


3-Year Code Cycle

#### **Investment Risk:**

Near-Term Obsolescence

#### Building Block #5: High-Efficiency Components





### **ENERGY STAR:**

Equipment
Lighting
Appliances
Fans

#### **Risk Driver:**

Optimized Enclosure

#### Outcome:


Heating/Cooling < 50% Load

#### **Efficiency Risk:**

Components Energy Use

# Building Block #6: Solar Ready Construction





#### **Solar Ready:**

Structural Calcs

Conduit for Wiring

**BOS Space** 

Extra Circuit
Breakers

**Risk Driver:** 

Optimized Enclosure Outcome:


Ultra-Low HVAC Eff. Components

Path to Zero Risk:

Zero Ready

## Zero Six Building Blocks Summary





Optimized Enclosure

Water Protection

Ensured Comfort

Indoor Air Quality Efficient Comps

Solar Ready

Complete Risk Management Systems



# Zero Energy Ready Home Training Zero Common Agenda

## Time for a Common Agenda



### 2015-16 ZE PROJECTS, BUILDINGS, & UNITS



741

PROJECTS 408 IN 2015



4,077

BUILDINGS 3,339 IN 2015



8,203

UNITS 6,177 IN 2015

NOT INCLUDING PLANNED UNITS/PROJECTS


- 33% BUILDINGS GROWTH IN A SINGLE YEAR
- 82% PROJECT GROWTH IN A SINGLE YEAR

Source: "To Zero and Beyond, Zero Energy Residential Buildings Study, 2016 Inventory of residential projects on the path to zero in the U.S. and Canada, Net Zero Energy Coalition, June 2017

# Time for a Common Agenda



### States with ZERH





# Zero:

- Name
- Strategy
- Threshold
- Simple Definition

# 'Net' Out:

- ProtectValuableReal Estate
- EnsureSimplicity





### Zero Name: Why 'Net' Out



# 'Net' Out:

- Protect Valuable Real Estate
- EnsureSimplicity



# 'Ready'

- Protect Core Customer Liability
- Inclusive vs.
   Exclusive

# **Substantial Uncertainty:**

- Software Predictions
  - HERS Predicted vs. Actual Energy Use
  - HERS Analysis Results Among Raters

# Occupant Impacts


- Number
- Equipment
- Behavior
- Maintenance

#### External Forces

- Year-to-Year Weather
- Utility Solar Power Purchase Charges

# **Don't Exclude Homes with:**

- Shading
  - Trees
  - Buildings
  - Architecture
- Low Insolation Locations
- Inadequate Roof Area
  - South-Facing
  - Multi-Stories






Optimized Enclosure System Water Protection System Optimized Comfort System Indoor Air Quality System

Efficient Comps System Solar Ready System

Six Complete Risk Management Systems



# High-performance home, so energy efficient,


all or most annual energy consumption can be offset by renewable energy.




# Zero Energy Ready Home Training Zero for Informed Buyers

### Informed Buyer Movement





# More Informed Homebuyers



SOURCE: National Association of Realtors® - Profile of Home Buyers and sellers 2010

## Informed Homebuyer Catalyst



## Informed Homebuyer Catalyst





**Facebook** 

**Twitter** 

By Nic Fleming

14 June 2017

## Informed Homebuyer Catalyst

Nearly three-quarters of Bristol residents who were shown thermal imaging of their home's heat loss took some kind of action.




### Cheap IR Cameras







### Mobile IR Cameras





### **Drone IR Cameras**



### Airborne IR Cameras







### Citywide IR Programs



How to ...

Search.....

3-1-1

Green Vancouver Your Government About Vancouver Parks, Recreation, and Culture Home, Property, and Development People and Programs Streets and Transportation Doing Business

Home > Green Vancouver > How you can go green > Programs to help reduce your footprint > At home > Thermal imaging program

### Green Vancouver

- Greenest City Action Plan
- Renewable City Strategy: our future to 2050
- Zero Waste Vancouver
- Climate Change
   Adaptation Strategy
- Neighbourhood Energy Strategy
- ▲ How you can go green
  - ▲ Programs to help reduce your footprint
    - At home
      - Smart Thermostat Pilot Program

Thermal Imaging program

At work

### Thermal Imaging program

We launched a thermal imaging pilot program in January to help homeowners identify energy loss in single family homes and to share information on energy saving incentives that are available. We've identified five neighbourhoods 1 (220 KB) to participate in the pilot. The images will be taken throughout the month of January and staff will follow-up with homeowners later this spring.

### What is a thermal image?

A thermal image is a picture of the heat that comes off of an object. Often in a thermal image, when something is hot, the image is bright yellow; if something is cold, it shows up as dark blue.

Thermal imaging is becoming an increasingly popular tool around the world to quickly identify opportunities for energy efficiency upgrades to a home that will also improve comfort and may improve health.

### Discover your home's energy efficiency potential

In Vancouver, 55% of all greenhouse gas (GHG) emissions come from buildings, and detached homes account for 31% of all GHG emissions from buildings.

Through the Greenest City Action Plan, we are aiming to reduce emissions from existing buildings by 20% by 2020. This would eliminate 160,000 tonnes of GHGs per year - the equivalent of removing 40,000 cars from the road.






### Buyers Will Know Thermal Defects









### **Buyers Will Know Thermal Defects**












## Builders Compete Thermal Defects ENERGY



#### Benefits of the GreenLean construction process

Based on the government's EnergyStar program, Haskell Homes has developed an exclusive new Green Lean construction process (patent pending) that catapults our homes to much higher levels of energy efficiency and green building than even the EPA suggests.

Competitor's Home



Thermal imaging can detect where homes are losing energy. In this picture of one of our major competitors houses the light areas represent heat loss during the winter. As you can see, heat is escaping from every board in the framing. This is due to the way the home was built, how it is insulated and several other factors. Haskell Homes built using the GreenLean construction method lose much less heat than what is being shown here. Because of GreenLean, every Haskell Home is able to save you as much as 50% on your utility costs. This translates to more money in your pocket each and every month you live in your home.

Our Home



This is a thermal image of a Haskell Home. As you can see, there is no heat loss from the framing inside the walls as there is in the picture of our competitor's house above. This is due to the GreenLean construction process which includes staggered 2 x 6 framing vs. standard 2 x 4 framing. It is also due to the better insulation used as well as many other unique construction techniques and attention to detail that make every Haskell Home have an HERS energy efficiency rating of 65 or less vs. a rating of 80 or above for many of our competitors' homes. Call us today at 801-298-8881 to learn more!



### Home Designs

Choose from 16 beautifully designed homes



### Locations

Build on your lot or ours across the Wasatch Front

# ...because it minimizes the risk of **Thermal Defects**


### **Buyers Will Know Poor Windows**



### **Buyers Will Know Poor Windows**




### Buyers Will Know Good Windows



# ...because it integrates Advanced Windows

## Buyers Will Know Moisture Problems **ENERGY**



## Buyers Will Know Moisture Problems **ENERGY**




# ...because it minimizes the risk of Moisture Defects



### Diagnostic System:

- Six Sensors[Outdoor Condenser]
  - 3 Thermal
  - 2 Voltage
  - 1 Current
- <15 Minutes Install</li>
- \$50 Hardware






### **Diagnostic Capability:**

- Charge [Low]
- Capacitor [Failed Start or Run]
- Flow [Condenser or Evaporator]
- Operation [Normal/Abnormal]
- Performance [COP]

### Buyers Will Know HVAC Quality



### Buyers Will Know HVAC Quality



# ...because it helps ensure Quality HVAC



### **Indoor vs. Outdoor Air Pollutants:**

On average 2-5 times greater

Up to 100 times greater

While Americans Spend

90% of time indoors

Source: EPA



"If your child doesn't use an inhaler, consider yourself a lucky parent because,

# 1 in 10 children in the U.S. suffers from asthma."

Source: Remarks for Administrator McCarthy, Announcement of Clean Power Plan, Washington, DC, June 2, 2014






## Buyers Will Know Indoor Air Quality **ENERGY**



Air Mentor


2015-02-05 10:10:53



# ...because it helps minimizes the risk of Health Problems


### Buyers Know Lack of Efficiency







"very energy efficient with low monthly utility costs."


**Source:** The Housing Satisfaction Gap: What People Want but Don't Have, Demand Institute, 2014






### **Buyers Will Know Asset Score**






### **Buyers Will Know Efficiency**



# ...because it optimizes Energy Efficiency

#### Buyers Know Solar Prices Falling



Source: "Solar Adds More Than 4 Gigawatts of Capacity in Q3, Marking its Largest Quarter in History, U.S. Solar Market Insight," Solar Energy Industry Association, Updated Dec. 13, 2016

#### Buyers Can See Solar



## ...because it optimizes Solar Readiness

#### **Buyers Know Planet is Hurting**








# Environmental Impact

#### Buyers Know Homes Are Aging






#### Buyers Know Homes Are Aging




#### Median Age of Housing Stock



- High Utility Bills
- Poor Comfort
- Health Concerns
- Moisture Issues
- Excessive Bugs/Pests
- **Durability Problems**
- Obsolete Technology

Meet 85% of Your Competition

## ...because it eliminates many liabilities with Older Homes




















#### ...because it delivers

# Trusted Performance

#### Buyers Will Know Reviews





#### Coming to a housing industry near you...



# ...because it helps optimize the Home Living Experience

#### Informed Buyer Rules\*



- 1. If it can be done, it will be done.
- 2. If you don't do it, someone else will.
- \* Daniel Burrus, "Flash Foresight"

#### • Film:

- Kodak
- Polaroid

#### Communication:

- Motorola
- Palm

#### Retail

- Too Many Retailers to Name
- Transportation:
  - American Car Manufacturers (close call)
  - TWA and other Legacy Airlines
  - Taxis
- ... and the list goes on...



#### Personal Transportation







Personal Transportation

Daily **Break** 



<1X 2-3X



Personal Transportation

Daily **Break**  Healthy Food







<1X 2-3X 2-3X



Personal Transportation

Daily Break Healthy Food

Tech + Design









<1X 2-3X 2-3X 10X

Personal Transportation

Daily **Break**  Healthy Food

Tech + Design Healthy Water











<1X 2-3X 2-3X

10X





#### Zero Energy Ready Home Training

#### **Zero Value Translated**

#### Zero Communication Challenge



# How do consumers decide?

































IECC

2009

#### Communication Strategy



- Simple Core Message
- Showcase Better Experience
- Clarity with Contrast



Home » Residential Buildings » Zero Energy Ready Home » DOE Tour of Zero


Are you ready for a home that lives, works, and lasts better? The home of the future - a better home - is available today. Take a virtual tour of homes that are so energy efficient a renewable energy system can offset all or most of their annual energy consumption. These award-winning homes are independently certified to meet DOE Zero Energy Ready Home guidelines and constructed by a select group of top builders. Zero Energy Ready Home is part of the U.S. Department of Energy's Better Buildings initiative. Better Buildings aims to make commercial, industrial, public, and residential buildings 20 percent more energy efficient over the next decade.



Click on a climate zone to see homes in that region.

Search: SEARCH RESET

Showing 1 to 25 of 123 entries







The home of the future...

Today





Buying a home is often the largest purchase of a lifetime with so much riding on getting it right.



This is because it's often cost-prohibitive to make substantial changes once a home is built.





Wouldn't it be great
to know what
leading experts
would look for in a
new home
that performs
to their expectations?





#### Well now you do.

When building performance professionals are polled, they overwhelming choose homes that meet Department of Energy Zero Energy Ready Home specifications.

#### **Seven Must-Have Systems**

1
Optimized
Thermal
Protection



Future Ready 2

Whole-House Water Protection



Moisture Ready 3

Advanced Heating and Cooling



Comfort Ready

4

High-Efficiency Components



Tech Ready

5 Comprehensive Indoor Air Quality



Health Ready 6

Solar Ready Construction




Zero Ready 7
Enhanced
Quality
Assurance



Performance Ready That's because leading experts know every certified Zero Energy Ready Home includes seven

must-have systems
that help ensure a
superior homeowner
experience.





Maybe most significantly, leading experts know all this added value, compared to a minimum code home, is available for lower ownership cost where significant utility bill savings exceed additional mortgage expenses.





In other words,
leading experts know
buying smart
is as easy as looking
for the DOE Zero
Energy Ready Home
label.






#### Zero Energy Ready Home for More Information:

https://energy.gov/eere/buildings/zero-energyready-home-homebuyers For more information how you can get the home experts would choose, visit the Zero Energy Ready Home web site.



### Housing Innovation Awards Feeds Tour of Zero





Home » Residential Buildings » Zero Energy Ready Home » DOE Tour of Zero

Are you ready for a home that lives, works, and lasts better? The home of the future - a better home - is available today. Take a virtual tour of homes that are so energy efficient a renewable energy system can offset all or most of their annual energy consumption. These award-winning homes are independently certified to meet DOE Zero Energy Ready Home guidelines and constructed by a select group of top builders. Zero Energy Ready Home is part of the U.S. Department of Energy's Better Buildings initiative. Better Buildings aims to make commercial, industrial, public, and residential buildings 20 percent more energy efficient over the next decade.



The Home of the Future ... Today

The Home of the Future Today Video (Text Version)

Showing 1 to 25 of 123 entries

Show 25 🗸 entries



Showing 1 to 13 of 13 entries (filtered from 123 total entries)

Show 25 V

TOUR THESE HOMES	BUILDER	LOCATION \$	HIA WINNER	CLIMATE ZONE
Air Park Drive	Addison Homes	Greer, SC	2016 HM	MIXED-HUMID
Cobbler Lane	Addison Homes	Greer, SC	2015	MIXED-HUMID
Invision Zero Home	Addison Homes	Greer, SC	2016	MIXED-HUMID
The Emery	Addison Homes	Greer, SC	2016	MIXED-HUMID
Friendly Home	Ferguson Design & Construction Inc.	Sagaponack, NY	2013	MIXED-HUMID
Julia Plan	Habitat for Humanity of Catawba Valley	Hickory, NC	2016	MIXED-HUMID
ne Villas at Rocketts Landing	Health E Community Enterprises of Virginia	Williamsburg, VA	2016	MIXED-HUMID
Euclid Avenue	Heirloom Design Build	Atlanta, GA	2015	MIXED-HUMID
High-Performance Bungalow	Imery & Co.	Athens, GA	2016	MIXED-HUMID
EXIT-O House	John Hubert Associates	Wyncote, PA	2014	MIXED-HUMID
Charlottesville Infill	Promethean Homes	Steeles Tavern, VA	2014	MIXED-HUMID
First DOE Zero Energy Ready Manufactured Home	Southern Energy Homes	Russellville, AL	2014	MIXED-HUMID
Proud Green Home	The Imery Group	Athens, GA	2014	MIXED-HUMID

Previous 1 Next



## DOE Tour of Zero: The Emery by Addison Homes

Home » DOE Tour of Zero: The Emery by Addison Homes







"THE DOE ZERO ENERGY READY HOME PROGRAM HAS SET A STANDARD THAT IS TRULY 'BEST IN CLASS' AND IS PULLING OUR INDUSTRY TOWARD A QUALITY REVOLUTION."

Consumer Experience



## DOE Tour of Zero: The Emery by Addison Homes

Home » DOE Tour of Zero: The Emery by Addison Homes









## DOE Tour of Zero: The Emery by Addison Homes

Home » DOE Tour of Zero: The Emery by Addison Homes









## DOE Tour of Zero: The Emery by Addison Homes


Home » DOE Tour of Zero: The Emery by Addison Homes














## **Showcase:** National Campaign



## Goal:

Inspire consumers to visit the home of the future... available today...

DOE Zero Energy Ready Homes.


## **Innovation Partners:**

- Manufacturers
- Associations
- Utilities
- Lenders




# Clarity depends on contrast.

We often understand something better when we see it in comparison with something else than when we see it in isolation.




# Clarity: ZERH Comparison Bars






## **Clarity:** Transparency









# **HEALTHFUL ENVIRONMENT**



KEY

DOE Zero Energy Ready Home

ENERGY STAR Home

Existing Home

This label indicates relative performance of this DOE Zero Energy Ready Home to existing homes (built between 1990 and 2010) and ENERGY STAR qualified homes. Actual performance may vary.







**Lives Better** 

Every DOE Zero Energy Ready Home has

a comprehensive package of measures to

minimize dangerous pollutants, provide

continuous fresh air, and effectively filter

HEALTHFUL ENVIRONMENT

the air you breathe

COMFORT PLUS

**Works Better** 

Every DOE Zero Energy Ready Home begins

STAR for Homes, and then adds advanced

technologies and practices from DOE's worldclass research program, Building America.

Compared to a typical home, an ultra efficient

Zero Energy Ready Home is inexpensive to

own. In fact, every DOE Zero Energy Ready

electric system can easily offset most, or all.

of your annual energy consumption. We call

Home is so energy efficient, a small solar

this Zero Net-Energy Ready.

with solid building science specified by ENERGY

ADVANCED TECHNOLOGY

**ULTRA EFFICIENT** 



## **Lasts Better**

#### QUALITY BUILT

Advanced construction practices and technologies are specified for every DOE Zero Energy Ready Home. Then they are enforced by Independent verifiers with detailed checklists and prescribed diagnostics.

The advanced levels of energy savings, comfort, health, durability, quality and future performance in every DOE Zero Energy Ready Home provide value that will stand the test of time, and will meet and exceed forthcoming code requirements.

LEARN MORE AT: buildings.energy.gov/zero

## The Future of Housing—Today

Only a select group of the top builders in the country meet the extraordinary levels of excellence and quality specified by U.S. Department of Energy guidelines.



LEARN MORE AT: buildings.energy.gov/zero



## A Symbol of Excellence

HEALTHFUL ENVIRONMENT

COMFORT PLUS

ADVANCED TECHNOLOGY

ULTRA EFFICIENT

QUALITY BUILT DURABILITY

KEY DOE Zero Energy Ready Home ■ ENERGY STAR Certifled Home

Existing Home

This label indicates relative performance of this DOE Zero Energy Ready Home to existing homes (built between 1990 and 2010) and ENERGY STAR Certifled Homes. Actual performance may vary.



durability unparalleled in today's marketplace.

Superior insulation, windows, air sealing and space conditioning systems included in every DOE Zero Energy Ready Home surround you

with even temperatures, low-humidity, and quiet in every room on every floor.

KEY DOE Zero Energy Ready Home ENERGY STAR Certified Home


Existing Home

**Inside Spread** 

Flap

**Back Cover** 

Front Cover







## **Lives Better**

#### HEALTHFUL ENVIRONMENT

Every DOE Zero Energy Ready Home has a comprehensive package of measures to minimize dangerous pollutants, provide continuous fresh air, and effectively filter the air you breathe.

## COMFORT PLUS

Superior insulation, windows, air sealing and space conditioning systems included in every DOE Zero Energy Ready Home surround you with even temperatures, low-humidity, and quiet in every room on every floor.

KEY DOE Zero Energy Ready Home

ENERGY STAR Certified Home Existing Home



## **Works Better**

#### ADVANCED TECHNOLOGY

Every DOE Zero Energy Ready Home begins with solid building science specified by ENERGY STAR for Homes, and then adds advanced technologies and practices from DOE's worldclass research program, Building America.

#### **ULTRA EFFICIENT**

Compared to a typical home, an ultra efficient Zero Energy Ready Home is inexpensive to own. In fact, every DOE Zero Energy Ready Home is so energy efficient, a small solar electric system can easily offset most, or all. of your annual energy consumption. We call this Zero Net-Energy Ready.



## QUALITY BUILT

Advanced construction practices and technologies are specified for every DOE Zero Energy Ready Home. Then they are enforced by Independent verifiers with detailed checklists and prescribed diagnostics.

The advanced levels of energy savings, comfort, health, durability, quality and future performance in every DOE Zero Energy Ready Home provide value that will stand the test of time, and will meet and exceed forthcoming code requirements.

LEARN MORE AT: buildings.energy.gov/zero







Front Cover

**Inside Spread** 

Flap

**Back Cover** 





"Our daughter couldn't breathe without discomfort for years. Within two months of moving into our new Cobblestone home

# we threw away the inhaler. That was priceless!"

Charly and Mary Jones, Cobblestone Homeowner









Smart vs.

Dumb

Cooling






# Smart vs. Dumb Heating



# Clarity: Translating Relative Value



# **Clarity:** Relative Value Confusion



## World's Best Window Co.

## Millennium 2000+

Vinyl-Clad Wood Frame Double Glazing • Argon Fill • Low E Product Type: Vertical Slider

## ENERGY PERFORMANCE RATINGS

U-Factor (U.S./I-P)

Solar Heat Gain Coefficient

0.35

0.32

## ADDITIONAL PERFORMANCE RATINGS

Visible Transmittance

Air Leakage (U.S./I-P)

0.51

0.2

Condensation Resistance

51

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

www.nfrc.org



# World's Better than Best Window Co.

Ultra-Millenium 3000+

Vinyl Extruded, UltraCore Frame Triple-Glazed \* Krypton 90, Low-E Product Type: **Vertical Slider** 

## **ENERGY PERFORMANCE RATINGS**

U-Factor (U.S./I-P)

Solar Heat Gain Coefficient

0.18

0.22

## ADDITIONAL PERFORMANCE RATINGS

Visible Transmittance

Air Leakage (U.S./I-P)

0.42

0.1


**Condensation Resistance** 

70

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. Consult manufacturer's literature for other product performance information.

www.nfrc.org

# **Clarity:** Relative Value Translated





# World's Better than Best Window Co.

Ultra-Millenium 3000+ Vinyl Extruded, UltraCore Frame Triple-Glazed \* Krypton 90, Low-E Product Type: Vertical Slider

Thermal Protection
Sun Protection
Natural Light
Draft Protection
Condensation Control

# 50-Year Window

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. Consult manufacturer's literature for other product performance information.

www.nfrc.org

specific product size. NFRC does not recommend any product and does not warrant the suitability of any

product for any specific use. Consult manufacturer's literature for other product performance information.

# Clarity: Relative Value Confusion







# Zero Energy Ready Home Training

# **Zero Builders in Action**

Builder 1 Builder 2



# Zero Energy Ready Home Training Zero Specifications

## Single-Family Detached



## Single-Family Attached




# Multi-Family Dwelling Units

- ≤ 5 Stories Above-Grade
- Individual HVAC
- Dwelling Units Occupy ≥ 80% Occupiable SF
- Individual or Central DHW (no solar required)



# Zero Energy Ready Home Spec







Optimized Enclosure System

Water
Protection
System


Optimized
Comfort
System

Indoor Air Quality System Efficient Comps System


Solar Ready System

Six Complete Systems for Risk Management

## **IECC Climate Zones**



# IECC Code Map



# Strategy: Align w/ENERGY STAR



- Building-Science
   Underpinning
- Variable vs. Fixed HERS Index Score
- House Size Adjustment
- Coordinated
   Performance Path







# ZERH / ESfH Spec Alignment

# **Mandatory** Requirements

Targeted 'Must-Have' **Innovations** 

Exhibit 1: DOE				

Area of Improvement		Mandatory Requirements
	ENERGY STAR for Homes Baseline	☐ Certified under ENERGY STAR Qualified Homes Version 3 <sup>5</sup>
2. Envelope <sup>6</sup>		□ Fenestration shall meet or exceed latest ENERGY STAR requirements <sup>7, 8</sup> □ Celling, wall, floor, and slab insulation shall meet or exceed 2012 IECC levels <sup>9</sup>
3.	Duct System	□ Ducts located within the home's thermal and air barrier boundary <sup>10</sup>
4.	Water Efficiency	☐ Hot water delivery systems shall meet efficient design requirements <sup>11</sup>
5.	Lighting & Appliances <sup>12</sup>	All installed refrigerators, dishwashers, and clothes washers are ENERGY STAR qualified.     80% of lighting fixtures are ENERGY STAR qualified or ENERGY STAR lamps (builbs) in minimum 80% of sockets     All installed bathroom ventilation and celling fans are ENERGY STAR qualified
6.	Indoor Air Quality	□ EPA Indoor airPLUS Verification Checklist and Construction Specifications <sup>13</sup>
7.	Renewable Ready <sup>14</sup>	□ EPA Renewable Energy Ready Home Solar Electric Checklist and Specifications <sup>15</sup> □ EPA Renewable Energy Ready Home Solar Thermal Checklist and Specifications <sup>10</sup>

# **Performance** Score

**Ensure Efficiency** with Trade-Off Flexibility

Exhibit	2.	DOF	Challenge	Home	Tarnet	Home 3	, 17

nvac Equipment							
	Hot Climates (2012 IECC Zones 1,2) 19	Mixed Climates (2012 IECC Zones 3, 4 except Marine)	Cold Climates (2012 IECC Zones 4 Marine 5,6,7,8)				
AFUE	80%	90%	94%				
SEER	18	15	13				
HSPF	8.2	9	10 <sup>20</sup>				
Geothermal Heat Pump	ENERGY STAR EER and COP Criteria						
ASHRAE 62.2 Whole-House Mechanical Ventilation System	1.4 cfm/W; no heat exchange	1.4 cfm/W; no heat exchange	1.2 cfm/W; heat exchange with 60% SRE				
Insulation and Inflitration							

Insulation levels shall meet the 2012 IECC and achieve Grade 1 Installation, per RESNET standards Infiltration21 (ACH50): 3 in CZ's 1-2 | 2.5 in CZ's 3-4 | 2 in CZ's 5-7 | 1.5 in CZ 8

	Hot Climates (2012 IECC Zones 1,2,)	Mixed Climates (2012 IECC Zones 3, 4 except Marine)	Cold Climates (2012 IECC Zones 4 Marine 5,6,7,8)			
SHGC	0.25	0.27	any			
U-Value	0.4	0.3	0.27			
James qualifying there up the Descriptive Dath with a total window to floor area greater than 159/ shall have adjusted						

U-values or SHGCs.25

ENERGY STAR minimum; for heating oil water heaters use EF = 0.60

# **Size Adjustment Factor**

Ensure Carbon Footprint

### Exhibit 3: Benchmark Home Size<sup>2</sup>

Bedrooms in Home to be Built	1	2	3	4	5	6	7	8
Conditioned Floor Area Benchmark Home	1,000	1,600	2,200	2,800	3,400	4,000	4,600	5,200

**Independent Verification** (HERS)

# **Mandatory Requirements**



Exhibit 1: DOE Zero Energy Ready Home Mandatory Requirements for All Labeled Homes

Area of Improvement		Mandatory Requirements
1.	ENERGY STAR for Homes Baseline	☐ Certified under ENERGY STAR Qualified Homes Version 3 or 3.1 <sup>9, 10</sup>
2.	Envelope <sup>11</sup>	<ul> <li>□ Fenestration shall meet or exceed ENERGY STAR requirements <sup>12, 13</sup></li> <li>□ Ceiling, wall, floor, and slab insulation shall meet or exceed 2012 or 2015 IECC levels<sup>14, 15</sup></li> </ul>
3.	Duct System	☐ Duct distribution systems located within the home's thermal and air barrier boundary or optimized to achieve comparable performance <sup>16</sup>
4.	Water Efficiency	☐ Hot water delivery systems shall meet efficient design requirements <sup>17</sup>
5.	Lighting & Appliances <sup>18</sup>	<ul> <li>□ All installed refrigerators, dishwashers, and clothes washers are ENERGY STAR qualified.</li> <li>□ 80% of lighting fixtures are ENERGY STAR qualified or ENERGY STAR lamps (bulbs) in minimum 80% of sockets</li> <li>□ All installed bathroom ventilation and ceiling fans are ENERGY STAR qualified</li> </ul>
6.	Indoor Air Quality	☐ Certified under EPA Indoor airPLUS <sup>10</sup>
7.	Renewable Ready	□ Provisions of the DOE Zero Energy Ready Home PV-Ready Checklist are Completed; (Solar Hot Water Ready provisions are encouraged but not required) <sup>19</sup>

## **Encouraged:**

- WaterSense Label (indoor and outdoor)
- Disaster Resistance (IBHS Fortified Home)
- Quality Management

# ZERH vs. ES Target Home Spec

## Exhibit 2: DOE Zero Energy Ready Home Target Home 7,20

Higher Eff. HVAC Equip.

Both 2012 IECC Insul. v3.1

HVAC Equipment <sup>21</sup>					
	Hot Climates (2012 IECC Zones 1,2) <sup>22</sup>	Mixed Climates (2012 IECC Zones 3, 4 except Marine)	Cold Climates (2012 IECC Zones 4 Marine 5,6,7,8)		
AFUE	80%	90%	94%		
SEER	18	15	13		
HSPF	8.2	9	10 <sup>23</sup>		
Geothermal Heat Pump ENERGY STAR EER and COP Criteria					
ASHRAE 62.2 Whole-House Mechanical Ventilation System	1.4 cfm/W; no heat exchange	1.4 cfm/W; no heat exchange	1.2 cfm/W; heat exchange with 60% SRE		
Inculation and Infiltration					

nsulation and Infiltration

Insulation levels shall meet the 2012 IECC and achieve Grade 1 installation, per RESNET standards.

Infiltration<sup>24</sup> (ACH50): 3 in CZ's 1-2 | 2.5 in CZ's 3-4 | 2 in CZ's 5-7 | 1.5 in CZ 8

Windows<sup>25, ,26, 27</sup>

	Hot Climates (2012 IECC Zones 1,2,)	Mixed Climates (2012 IECC Zones 3, 4 except Marine)	Cold Climates (2012 IECC Zones 4 Marine 5,6,7,8)
SHGC	0.25	0.25	any
U-Value	0.4	0.3	0.27

Homes qualifying through the Prescriptive Path with a total window-to-floor area greater than 15% shall have adjusted U-values or SHGCs.<sup>28</sup>

#### Water Heater

ENERGY STAR levels for the system Energy Factor, as follows:

- Gas/propane systems of ≤ 55 gallons, EF = 0.67
- Gas/propane systems of > 55 gallons, EF = 0.77
- Electric systems, EF = 2.0

For heating oil water heaters use EF = 0.60

## Thermostat<sup>29</sup>

Programmable thermostat (except for zones with radiant heat)

### Lighting & Appliances


 For purposes of calculating the DOE Zero Energy Ready Home Target Home HERS Index, homes shall be modeled with an ENERGY STAR dishwasher, ENERGY STAR refrigerator, ENERGY STAR ceiling fans, and ENERGY STAR lamps (bulbs) in 80% of sockets or 80% of lighting fixtures are ENERGY STAR Qualified. Half ACH50

More Eff. Windows

ENERGY STAR vs. Min. WH

# ZERH Average HERS Scores





Based on 1800, 2400, and 3600 ft <sup>2</sup> prototypes on climate-appropriate foundations.

### Size Adjustment Factor



Homes larger than the benchmark home size must use the size adjustment factor to determine the target HERS index

Exhibit 3: Benchmark Home Size26

Bedrooms in Home to be Built	1	2	3	4	5	6	7	8
Conditioned Floor Area Benchmark Home	1,000	1,600	2,200	2,800	3,400	4,000	4,600	5,200

**Note:** Renewable energy systems may not be used to qualify for the ZERH HERS Index Target Score, but may be used for the *incremental* HERS Index points needed for the Size Adjustment Factor.

Size Mod. Factor =  $[CFA_{Benchmark Home}/CFA_{Home to Be Built}]^{0.25}$  [Not to Exceed 1.0]

# Performance Path Example CZ2 Prototype - 4 BR, 3500 SF



Specification	Target Home Spec	Design Home
Mandatory Items: ducts in conditioned space; 2012 IECC insulation; etc.		Meets all mandatory items; uses total UA to meet insulation reqmnt.
Windows	U=0.40; SHGC=0.25	U=0.32; SHGC=0.24
Infiltration	3 ACH50	2.5 ACH50
Duct Leakage	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	Total leakage ≤ 280 CFM25 Leakage to outdoors ≤ 140 CFM25
Furnace AFUE	80	92
A/C SEER	18	16
Whole-House Mech. Vent.	75 cfm; 1.4 cfm/W;	75 cfm; 5.0 cfm/W
Water Heater	ENERGY STAR	Gas storage 0.67 EF
Target Home HERS Index	55; ( <b>52 with SAF</b> )	
HERS Index – Design Home		52 – COMPLIES!

# Rating & Verifying Homes



- Same: ENERGY STAR Homes framework
- New:
  - Indoor airPLUS Checklist;
  - Renewable Energy Ready Home Checklists (if req'd.)
  - Hot Water Distribution test
- Submissions:

**Current:** Send "DOE ZERH Verification Summary" electronically to <a href="mailto:zero@newportpartnersllc.com">zero@newportpartnersllc.com</a>

**Future:** Automatically submitted as part of rating to RESNET National Homes Registry

#### ZERH Technical Resources



- Technical Webinars
- Webinar Meetings
- Building America Solution Center (BASC)
- Building America Research Studies
- Leading Builder Round-Table Meetings

For Info: www.buildings.energy.gov/zero/




# Zero Energy Ready Home Training


Zero Specifications

# **Optimized Enclosure**

# Zero Energy Ready Home Spec










2012 / 2015 IECC **Envelope Insulation Tighter Construction ENERGY STAR Windows** 





# Optimized Enclosure is Part of Complete Building Science System






# Rate of Thermal Flow:

A well-insulated and air-sealed home, with good windows and doors, reduces the amount of energy needed to keep the home comfortable.




# Energy moves from more to less...







# Energy moves from more to less...





# Energy moves from more to less...






1, 000 sq. ft. **R-38 Attic** U = .026

Drop-Down Stair = R-1

R-1, U = 1.0

10 sq. ft. = 1% of area

What Percent Loss in Attic R-Value?




Avg. U-value

$$= \frac{U1 \times A1 + U2 \times A2 + ...}{\text{Total Area (A)}}$$

$$= \frac{(.026 \times 990) + (1 \times 10)}{1,000}$$

$$=\frac{35.74}{1,000}=.036=$$
**R-28**

1% Hole Results in 27% Lower R-Value (R-28 vs. R-38)



Assume 50° F temp difference at attic ceiling

Heat Flow =  $U \times A \times \Delta T$ 

#### **Heat Flow without Hole**

 $= .026 \times 1,000 \times 50$ 

= 1316 Btu/hr

#### **Heat Flow with Hole**


 $= .036 \times 1,000 \times 50$ 


= 1786 Btu/hr


33%+ >Heat Flow with 1% Hole

# Thermal Holes Are a Big Deal











# Optimized Enclosure System



- Air-Tight Construction
- Complete Air Barriers
  - Thermal Bypass
  - Wind Intrusion
- Insulation System
  - Next Code Quantity
  - Proper Installation
  - Minimum Thermal Bridging
- Advanced Windows

Air and Thermal Flow Control



### Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure

# **Air-Tight Construction**

#### Why Air-Tight Construction



- 16 to 50% of HVAC Loads
- Moisture Problems
- Comfort Problems
- Indoor Air Quality

# Target Home Air-Tightness



	ACH50 Requirements/Targets				
Climate Zones	Zero Energy Ready Home	ENERGY STAR V3	2012 IECC	Passive House	
1-2	3.0	6.0	5. 0	0.6	
3-4	2.5	5.0	3.0	0.6	
5-7	2.0	4.0	3.0	0.6	
8	1.5	3.0	3.0	0.6	

#### Seal Usual Suspects



#### **Cracks:**

- Sill Plates
- Windows & Doors
- Drywall at Top Plate
- Access Panels
- Sheathing Joints
- Foundation/Framing

#### **Penetrations:**

- Plumbing
- Wiring
- Recessed Lights
- Vents
- HVAC Duct Boots

#### **Shafts:**


- Flues
- Ducts
- Plumbing

#### **Odd Geometry:**

- Cantilevers
- Knee-walls



# What We're Trying to Avoid





# Default: Spray Foam



Alternative: Sill sealer




Alternative: Constr. Adhesive




### Air Leakage Distribution

Exterior air barrier Cathedral ceiling


Sheathing / roof joint 1.1 cfm/ft @ 50 Pa







■ Stud / top plates

■ Top plates















2-Story house (Floor area = 2,000 ft<sup>2</sup>) Sheathing / roof joint unsealed  $\approx 0.5 \text{ ACH}_{50}$ 

	DOE Zero Ready		IECC 2012		
Zones	Requirement	Contribution to requirement (%)	Requirement	Contribution to requirement (%)	
1 – 2	3	17	5	10	
3 – 4	2.5	20	3	17	
5 – 7	2	25	3	17	
8	1.5	33	3	17	

### Rectangular Electrical Box












- 1/8" to 1/4" perimeter gap
- ~ 12 cfm @ 50 Pa
- Perimeter gap sealed
  - Somewhat effectively with one-component polyurethane foam
  - Effectively with caulk
- Wire holes ≥ 50% of leakage



Air leaked at nailed fasteners




Repeat test with screwed fasteners

#### **Exterior Air Barrier:**

2-Story House (2,000 sq. ft.)

(4) Elect. Outlets =  $0.17 \text{ ACH}_{50}$ 

Exterior Sheathing/Foundation  $= 0.51 ACH_{50}$ 



(5) Lights = 0.29 ACH<sub>50</sub>

Ext. Sheathing/Roof  $= 0.51 ACH_{50}$ 

Air barrier

= 0.51

Duct  $\approx 0.22$  ACH<sub>50</sub>

- Sheathing/Foundation Joint Unsealed
- 2. Sheathing/Roof Joint Unsealed = 0.51
- 3. (4) Electrical Outlets = 0.17
- 4. (5) Ceiling Lights = 0.29
- 5. Return Duct = 0.22


1.7 ACH<sub>50</sub>

# Sealing HVAC Ducts with Aeroseal



# Air Sealing Homes with Aerosol





Photos from wcec.ucdavis.edu



Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure

# High-Perf. Insulation System


# High-Perf. Insulation System



- Complete Air Barriers
- Quality (Installation)
- Quantity (High-R)
  - Walls
  - Roof
  - Foundation

# 2012 & 2015 IECC Requirements





ONLY Change in U-Value is for Above-Grade Framed Walls

No Changes to Prescriptive R-Value Requirements

Climate Zone	2012 U-Factor Equivalent Above- Grade Frame Wall (Table 402.1.3)	2015 U-Factor Equivalent Above-Grade Frame Wall (Table 402.1.4)	<b>Change</b> (% and Direction)	
1	0.082	0.084	2% Decrease in Stringency	<b>4</b>
2	0.082	0.084	2% Decrease in Stringency	•
3	0.057	0.060	5% Decrease in Stringency	•
4 except Marine	0.057	0.060	5% Decrease in Stringency	•
5 and Marine 4	0.057	0.060	5% Decrease in Stringency	<b>4</b>
6	0.048	0.045	6% Increase in Stringency	<b>↑</b>
7 and 8	0.048	0.045	6% Increase in Stringency	<b>1</b>

- No additional burden for most designs
- In Climate Zones 1 5, meeting 2015
   IECC via a whole-building UA tradeoff will be very slightly less stringent
  - Required Frame Wall U-Factor is 2 to 5% less stringent
  - Frame Walls might comprise ~ 20% 40% of total shell area...

#### 2012 IECC Insulation




- Compliance with next generation code
- Three Options:
  - ✓ Prescriptive
  - ✓ Alternative equivalent U-factor
  - ✓ Total UA calculation [allows window to be included]
- Allowances for ceilings without attic spaces [up to 500 square feet or 20% of roof area, whichever is smaller]

#### 2012 IECC Insulation




	CZ 2	CZ 3
Walls	R-13 (rec. R13+5)	R-20 or R-13+5 (rec. R-13+5)
Ceiling	R-38	
Floor	R-13	R-19
Basement	R-0	R-5/13
Crawl Space	R-0	R-5-13
Slab	R-0 (rec. R-5 slab edge)	






#### High-Perf. Insulation Guidance Tool









#### Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure System
Insulation System

# **Complete Air Barriers**

#### Complete Air Barriers



#### **Walls**


- Showers and Tubs
- Fireplaces
- Attic Knee Walls
- ☐ Skylight Shaft Walls
- Adjoining Porch Roof
- Staircase Exterior Walls
- Double Walls
- □ Rim/Band Joists
- Other Exterior Walls

#### **Floors**

- ☐ Floors Above Garage
- Cantilevered Floor
- ☐ Unconditioned Floor (Basement/Crawl Sp.)

## **Ceilings**

- Dropped Ceiling/Soffit atUnconditioned Attic
- □ Other Ceilings



# Air Barrier Example: Attic Knee Wall



No rigid backing on knee wall.



Rigid backing installed prior to insulation.

# Air Barrier Example: Garage Rim Joist



No air barrier is present between garage and conditioned space.



Air barrier is present between garage and conditioned space.

# Air Barrier Example: Wall Adjoining Porch Roof



No air barrier between porch attic and conditioned space.



Air barrier is installed prior to porch attic framing.



#### Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure
Insulation System

High-R Walls

#### High-R Wall Options



## Advanced Framing

- Thicker Wall
- Staggered Studs
- Double Wall

## Rigid Insulation Exterior Sheathing

- With Sheathing
- Without Sheathing
- With Extended Plate and Beam
- With Structural Engineered Panel

### Systems Building

- Structural Insulated Panels (SIPs)
- Insulated Concrete Forms (ICFs)
- Insulated Concrete Panels (ICPs)
- Precast Concrete

#### Adv. Framing w/Thicker Walls



- R-17 R-21 (U 0.052-0.060)
- Higher Framing Factor (~12-15%)
- Blanket Insulation Issues:
  - R-19 is 6" Thick, Compressed is R-17
  - R-21 is 5.5" Thick, Uncompressed is R-21
- Blown-In Insulation Issues:
  - Settling
  - Proper Density (Bag Count)
- Spray Foam Issues:
  - High Cost
  - Closed Cell Enhances Structure Perf.
  - Still Need to Ensure Quality installation



## Adv. Framing: Staggered Studs



- 2x6 plates with 2x4 staggered studs at 12"/24" o.c.
- Reduces thermal bridging by 80-90%
- Cost competitive with traditional 2x6 wall
- Need to ensure spacing between studs okay for deflection



## Adv. Framing: Double-Wall

- R-26 Walls (U ~ 0.034)
- Studs Offset or Separated for Complete Thermal Break
- Coldest Outside Sheathing Needs to Ensure Drying
  - Vapor-open designs use higherperm sheathing such as plywood or exterior-grade gypsum board
  - Modeling needed to assure moisture control
  - Class I Vapor Retarder (e.g., airtight drywall)
- Same Framing Techniques
   Already Understood by Trades



Climate Zone	Class III vapor retarders permitted for:
Zone Marine 4	Vented cladding over OSB
	Vented cladding over plywood
	Vented cladding over fiberboard
	Vented cladding over [exterior] gypsum [sheathing]
	Insulated [foam] sheathing with R-value ≥ R2.5 over 2x4 wall
	Insulated [foam] sheathing with R-value ≥ R3.75 over 2x6 wall
Zone 5	Vented cladding over OSB
	Vented cladding over plywood
	Vented cladding over fiberboard
	Vented cladding over [exterior] gypsum [sheathing]
	Insulated [foam] sheathing with R-value ≥ R5 over 2x4 wall
	Insulated [foam] sheathing with R-value ≥ R7.5 over 2x6 wall
Zone 6	Vented cladding over fiberboard
	Vented cladding over [exterior] gypsum [sheathing]
	Insulated [foam] sheathing with R-value ≥ R7.5 over 2x4 wall
	Insulated [foam] sheathing with R-value ≥ R11.25 over 2x6 wall
Zones 7 and 8	Insulated [foam] sheathing with R-value ≥ R10 over 2x4 wall
	Insulated [foam] sheathing with R-value ≥ R15 over 2x6 wall

## Rigid Insulation w/Sheathing



## How Much Rigid Insulation Thickness:

Climate Zone	Min. R-Value Foam Sheathing	
	2x4 Walls	2x6 Walls
1-4 Except Marine	Any	Any
Marine 4	R-2.5	R-3.75
Zone 5*	R-5	R-7.5
Zone 6*	R-7.5	R-11.5
Zone 7 and 8*	R-10	R-15

<sup>\*</sup> Exempt from Class 1 Vapor Retarder; Class III okay (e.g., Latex Paint)

Source: IRC 2007 Supplement, Table N1102.5.1

#### Rigid Insulation w/Sheathing




- R-18 Wall (U 0.054)
- Complete Thermal Break
- Condensation Surface Outboard Structure
- Can Combine Sheathing w/ Weather Resistant Barrier
- Installation Issues:
  - ≤ 1.5" Thick, Nails Okay
  - > 1.5" Thick, Screws Needed



#### Rigid Insulation w/o Sheathing



- R-17-R-28 Wall
- Complete Thermal Break
- Enhanced Racking Strength and Impact Resistance with CCSpf Enables No Sheathing
- Rigid Insulation Sheathing serves as Weather Resistant Barrier w/Liquid Membrane at Joints and Pan Flashing
- Class III Vapor Barrier (Latex Paint)
- Substantially Reduced Framing including Single Plates
- Engineered Stamped System
- Cost Competitive



#### Rigid Insulation w/Extended Plate



- R-18 Wall
- 2x4 Studs with 2x6 Plates
- Sheathing Attached to Plates for Near Full Racking Strength
- Complete Thermal Break Except for Top and Bottom Plates
- Condensation Surface Inside
   Assembly, so Must Control Air Flow
- Cladding Attachment Simplified if Permissible to Nail to Sheathing





- Innovative & Affordable
- Based on the perfect wall, using a "studless" structural engineered panel
- Single water, air, and vapor control layer
- Recent experience has demonstrated it can be built for less than a standard wood-frame wall system

























### Structural Insulated Panels (SIPs)




- R-26 Walls (6") (U 0.034)
- Substantial Thermal Break
   (3 8% Framing Factor)
- Special Construction Practices Required
- Foundation has to be Perfectly Level
- Significantly Reduced Time-of-Construction
- Reduced Dimensional Variation Corrections
- Killer Applications



- ~R-24 Walls (U 0.038)
- Complete Thermal Break
- Useful Thermal Mass
- Foundation has to be Perfectly Level
- Longer Time-of-Construction
- Maximum Disaster Resist.
- Termite Resistant
- Reduced Dimensional Variation Corrections
- Much More Costly





- ~R-24 Walls (U 0.038)
- Complete Thermal Break
- Useful Thermal Mass
- Foundation has to be Perfectly Level
- Significantly Reduced Time-of- Construction
- Maximum Disaster Resist.
- Termite Resistant
- Reduced Dimensional Variation Corrections
- Cost Competitive





#### ICP Installation Steps



Panels
As
Delivered






#### Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure System
Insulation System


# **High-R Foundation**






# High-R Foundation Slab Edge Insulation Options








a + b = insulation depth

# High-R Foundation: Unvented Crawlspace





# High-R Foundation: Unvented Crawlspace Exemptions



- Flood Zone Areas
- Raised Pier Foundation with No Walls
- Dry Climates per 2009 IECC
- Marine Climates per 2009 IECC Where No Air Handler or Return Ducts

**Note:** Vented crawl space will have floor insulation per 2012 IECC installed to RESNET Grade 1




### Zero Energy Ready Home Training

Zero Specifications
Optimized Enclosure
Insulation System

High-R Roof


### High-R Roof Insulation at Flat



#### High-R Roof Insulation at Slope



5.1 AIR-IMPERMEABLE: In direct contact with the underside of the sheathing



#### Minimum R-value of Impermeable Insulation

Climate Zone	Minimum Impermeable Insulation R-Value*	2012 IECC Ceiling R-Values
2B and 3B Tile Roof	None Required	30
1, 2A, 2B, 3A, 3B, 3C	R-5	38
4C	R-10	38
4A, 4B	R-15	49
5	R-20	49
6	R-25	49
7	R-30	49
8	R-35	49


<sup>\*</sup>contributes but doesn't supersede 2012 IECC insulation requirements

#### Top Insulated Roof Deck




**bsc** Building Science

Corporation





- Remove existing roofing and underlayment; Inspect existing roof deck and framing and repair as necessary.
- 2) Install new exterior foam board insulation, roof sheathing, underlayment, flashings and roofing.
- Remove existing soffit and install rigid blocking to prevent loose-fill fiber insulation from blowing into soffit; Install continuous air seal at all joints and interfaces in blocking; Replace soffit.
- 4) Dense-pack rafter cavities using approved cellulose or glass fiber insulation and following insertion tube techniques described in BPI RBE-WHALCI 2012.




#### Why Two Layers Rigid Foam



#### Guidance for Dense Pack Roof







### Zero Energy Ready Home Training


Zero Specifications
Optimized Enclosure

## **Advanced Windows**

#### **ENERGY STAR Windows**



- Assures beyond-code window performance
- Fenestration used for passive solar design are exempt from the U-factor and SHGC requirements
- Area-weighted averages for U-factor, SHGC permitted




#### Good, Better, Best Windows



	Hot Climates IECC CZ 1-2		Mixed Climates IECC CZ 3-4 except Marine		Cold Climates IECC CZ 5-8 and 4 Marine	
	U-value	SHGC	U-value	SHGC	U-value	SHGC
Mandatory: ENERGY STAR	0.40	0.25	0.30	[4] <b>0.40</b> [3] <b>0.25</b>	0.27 0.28 0.29 0.30	Any ≥0.32 ≥0.37 ≥0.42
Performance: Target Home	0.40	0.25	0.30	0.25	0.27	Any
<b>Encouraged:</b> High-R			0.21	0.25	0.18 - 0.21	Any

## Why Go Beyond ENERGY STAR\* ENERGY

Window 15% of Wall Area	Wall R-Value with Windows w/Varied Wall Insulation Levels				
U-Value	R-0	R-18	R-39	R-60	
0.30	R-5	R-11	R-15	R-17	
0.20	R-5	R-13	R-19	R-23	
0.15	R-5	R-14.5	R-23	R-28	
0.10	R-5.5	R-16	R-27	R-34	



#### \* In Cold Climates

#### Sources:

"Holes in the Wall: To Improve the Energy Performance of Walls, Look at the Total R-Value," Journal of Light Construction, February 2014;

Multi-Assembly R-Value / U-Value Calculator — Cascadia Windows and Doors; Michael Blasnik Presentation, 2014 ACI Conference

### The Biggest Thermal Hole....





## Zero Energy Ready Home Training

Zero Specifications

## **Water Protection**

### Zero Energy Ready Home Spec

Water Protection System










- Sump Pumps
- Flooring Materials
- Sub-Slab Aggregate



#### **Bulk Moisture Control Concept**



#### **Bulk Moisture Control**




- Weather Resistant Barriers
- Flashing
- Capillary Breaks

Water Management

#### What We're Trying to Avoid





Missing step & kick-out flashing

#### Step & Kick-Out Flashing







## Zero Energy Ready Home Training


Zero Specifications

## **Ensured Comfort**


#### Zero Energy Ready Home Spec













 RH Control In Hot/Humid Climates





## Quality HVAC Installation:

- High efficiency
- Properly designed and installed
- Combined with a duct system that's insulated, sealed, and balanced
- ... Maintain comfort with less energy.
- Ducts in Conditioned Space:




### Zero Energy Ready Home Training

Zero Specifications
Ensured Comfort

# Quality HVAC Installation




### Energy moves from more to less.






### Energy moves from more to less.




Cooling Load varies for each hour of the year.


 Cooling Peak Load: Maximum energy added in a single hour, and must be removed to maintain temperature and humidity.




- Cooling & heating equipment are "btu machines" that add or remove btu's to offset the load
- Load = number of btu's equipment has to remove or add
- Load independent of <u>type</u> of equipment used



Heating and cooling equipment generally two modes – on & off.




Equipment < Load



Equipment > Load

### What We're Trying to Avoid








Verify that the equipment capacity is right-sized relative to the heating and cooling load.

#### **Duct System Design**



1. Air follows the path of least resistance.




equal flow

less flow



#### Factors that influence the airflow of the ducts:

- Duct Length
- Duct Size
- Duct Shape
- Duct Type
- Duct Turns
- Other Components (e.g., Filters)



### What We Are Trying to Avoid





Verify that the ducts are balanced, insulated, tight, and installed without major defects.

## **Basic Concepts HVAC QI**



## Design:

- 1. Calculate Heating/Cooling Loads
- 2. Select Equipment that Meets Loads
- 3. Design Duct System that Gets Air from Equipment to Rooms and Back

## **Commission:**

- A. Check Airflow at Air Handler
- B. Check Refrigerant Charge
- C. Measure Airflow at Registers/Exhaust

HVAC QI Contractor Checklist

Rater Field Checklist



## Zero Energy Ready Home Training

Zero Specifications
Ensured Comfort

## **Ducts in Conditioned Space**

## Significant Thermal Losses:


- Thermal losses triple for ducts in unconditioned vs. conditioned space
- Total thermal losses can range from 10-45%
- Extensive unconditioned space penetrations

## Significant Performance Impacts:


- IAQ
- Comfort
- Durability

- Short Duct Run
  - up to 10' of total length is permitted to be outside of the home's thermal and air barrier boundary.
- Jump Ducts
  - may be located in attics if all joints, including boot-todrywall, are fully air sealed with mastic
- Ductless HVAC system


#### **Ducts in Conditioned Space**




**Ducts in Dropped Ceiling** 




**Ducts in Modified Attic Truss** 




**Ducts Between Floors** 



Ducts in Unvented
Crawl Space/Basement



**Ducts in Unvented Attic** 



**Ducts in Vented Attic** 

# Ducts in Conditioned Floor Space Option 1: Dropped Ceiling






- Architectural Integration
- Good Fit w/Simple Plans
- Longer Throws (ACCA Man T)




# Ducts in Conditioned Floor Space Option 2: Modified Attic Truss




Ducts in modified truss in attic

- Design Integration
- Good Fit w/Narrow Plans
- Sealed Air Barrier Critical





## Ducts in Conditioned Floor Space Option 3: Ducts Between Floors



Ducts between floors


- Simple Installation
- Design Flexibility
- Cost-Effective
- Floor Registers Likely



# Ducts in Conditioned Floor Space Option 3: Ducts Between Floors



## Unvented Crawl Space/Basement




Ducts in unvented crawl space or basement

- Simple Installation
- Design Flexibility
- Cost-Effective
- Floor Registers Likely



#### **Ducts in Unvented Attic**





Ducts in unvented attic

- CZ 5+, air impermeable plus a Class II VR or Class III VR in direct contact
- No Class I VR on attic floor





#### Enhanced Performance:


- Ducts and air handler in conditioned space
- Enable fire sprinklers that don't undermine the thermal and air control layer

## Cost Savings:

- Eliminate ~dozen thermal bypass air barrier details
- Additional storage, especially in slab-on-grade homes
- Eliminate need for soffit and roof vents
- Enabling single- rather than dual-zone HVAC systems by eliminating the egregious attic interface

## Ducts in Vented Attic: Dry CZs






Ducts in vented attic

#### **Issues:**

- R-8 duct insulation min.
- Ductwork buried min. 3.5" blown-in insulation
- Total duct leakage ≤ 3
   CFM25 per 100 ft<sup>2</sup> CFA
- Air Handler must be inside conditioned space






Blown-in Insulation R-8 Duct


**Truss Lower Chord** 

#### Ducts in Vented Attic: Humid CZs




Ducts in vented attic **Issues:** 

- R-8 duct insulation min.
- 1.5" minimum of ccSPF encapsulating ducts
- Ductwork buried min. 2" blown-in insulation
- Total duct leakage ≤ 3
   CFM25 per 100 ft<sup>2</sup> CFA
- Air Handler must be inside conditioned space




# Buried Encapsulated Ducts (BEDs) (~R-25)



**Truss Lower Chord** 

## Buried Encapsulated Duct (BED)



Ducts buried under loose-fill insulation

R-8 ducts encapsulated in 1.5" ccSPF

R-8 flex duct encapsulated in 1.5" ccSPF

Duct boot connection encapsulated in 1.5" ccSPF

Drywall ceiling

Truss lower chords




# Zero Energy Ready Home Training Zero Specifications Indoor Air Quality

## Zero Energy Ready Home Spec













- Radon Resistant
- Low Emission Materials
- Combustion Safety
- High MERV Filter



## Why IAQ is NOT A La Carte?



- 2000 SF Home
- 8.5' Ceilings
- 3 ACH50 Air Tightness
- 200 cfm Exhaust (e.g. dryer, range hood)
  - 5 Pa depressurization



## Indoor Air Quality as a System

Source Control

Dilution

Filtration

Practices & Product Selection
That Limit:

- Moisture
- Radon
- Chemicals
- Combustion By-Products
- Biological Contaminants

HVAC Quality Installation System



- Moisture Vapor:
  - Air Sealing
  - Air Barriers
  - Vapor Barriers/Retarders


Thermal Enclosure System

- Bulk Moisture:
  - Water-Managed Roofs
  - Water-Managed Walls/Openings
  - Water Manage Foundation/Site
  - Water Managed Materials

Water
Managed
Construction

- Internal Moisture Control:
  - HVAC Quality Installation
  - Whole-House Ventilation
  - Sport Ventilation
  - Dehumidification [Warm-Humid Climates]

**HVAC System** 



Equipment with sufficient latent capacity to maintain indoor relative humidity (RH) ≤ 60%:

Additional dehumidification system(s), OR

A central HVAC system equipped with


additional controls to operate in

dehumidification mode.

Dust mites in the billions at 60% RH or higher








Surgeon General's Warning: Radon Causes Lung Cancer

average risk by county.

However, High levels of Radon can be found in any home.



#### Required for Moisture Control:

- A. Gas Permeable Layer (min. 4" clean gravel)
- B. Plastic Sheeting (under slab)
- C. Sealing and Caulking (all openings in concrete floor)
- D. Vent Pipe (3 or 4 inch PVC pipe)
- E. Junction Box (if fan needed later)

Radon Test Kits Not Required

# Source Control: Biological Contaminants Pests



## Source Control: Biological Contaminants Screened Openings for Pests





Corrosion-proof rodent/bird screens for openings (e.g., copper or stainless steel mesh)

Exception: clothes dryer vent

# Source Control: Biological Contaminants/Moisture Foundation Sealing



Sealed Sump Pump



Air Sealing

# Source Control: Combustion By-Products Power/Direct Vent Equipment




Power Vented Water Heater



**Direct-Vent Furnace** 

## Source Control: Combustion By-Products Certified Fireplaces & Stoves









- Vented to outdoors
- Adequate Combustion and Ventilation Air
- Gas fireplace power or direct vented
- Meet Specified Standards

## Source Control: Combustion By-Products Certified CO Alarms



#### CO Alarm in each bedroom area



**CO Alarm** 



Combined CO & Smoke Alarm



# Enforceable policy in Multi-family buildings



# Source Control: Combustion By-Products Attached Garage Isolation





# Exhaust Fan Optional






# Source Control: Combustion By-Products Attached Garage Isolation




No Air Handler in the Garage



Picture Source: Construction Instruction




#### MDF & Particleboard





## Source Control: Chemicals Low Formaldehyde Cabinets





- Visit <u>www.kcma.org</u>
- Follow Industry Professional link to Environmental Stewardship Program



#### Health Hazards of VOCs

VOLATILE Organic Compounds

#### Immediate

- Eye & Respiratory Tract Irritation
- Headaches
- Dizziness
- Visual Disorders
- Memory Impairment

#### Up to 6 years

- Eye, Nose, and Throat Irritation
- Headaches
- Loss of Coordination
- Nausea
- Damage to Liver, Kidney, and Central Nervous System
- Cancer



## Source Control: Chemicals Low VOC Paints

Interior paints and finishes, including 90% or more of such products applied to interior surfaces of homes, shall be certified low-VOC or no-VOC by one of the following:



- Green Seal Standard GS-11, OR
- Greenguard Certification for Paints and Coatings, OR
- Scientific Certification Systems (SCS) Standard EC-10.2-2007, Indoor Advantage Gold, OR
- Master Painters Institute (MPI) Green Performance Standards GPS-1 or GPS-2, OR
- A third-party low-emitting product list based on CA Section 01350, e.g., the CHPS List at chps.net/manual/lem\_table.htm.

Carpets and carpet adhesives shall be labeled with, or *otherwise* documented as meeting, the Carpet & Rug Institute (CRI) Green Label Plus or Green Label testing program criteria. Carpet cushion (i.e., padding) shall similarly be certified to meet the CRI Green Label testing program criteria.



# Source Control: Chemicals Identifying Low-Emission Solutions



- Low emission materials and products are rapidly evolving, gaining market share & recognition
- Standards, labels, certification agencies can be challenging to navigate
- To help partners identify sources and spec products, a new IAP resources is available:

How to Find Indoor airPLUS
Compliant Low-Emission Products



#### Cabinetry Requirement: Use Cabinetry made with component materials (plywood, particleboard, MDF) that are certified to comply with the appropriate standards above; OR registered brands or products produced in plants certified under the Kitchen Cabinet Manufacturers Association's (KCMA) Environmental Stewardship Certification Program (ESP 05-12); OR GREENGUARD or GREENGUARD Gold Certification for Cabinetry. Meet at least one standard How to find compliant products below KCMA's Environmental Look for the KCMA-ESP label on cabinets (often sink bases), product Stewardship Program (ESP packaging, and/or spec sheets. 05-12) For a list of KCMA certified manufacturers that produce compliant cabinets, visit: http://www.kcma.org/Members/ **ESP Certified Manufacturers** Note: Manufacturers listed in the link above can be used as a resource, but partners should request confirmation from the manufacturer or supplier that the product lines they are using are indeed compliant.



## Three Options:

- Exhaust-Only
- Supply-Only
- Balanced

ASHRAE 62.2 2010 Continuous Ventilation Rate:

 $[7.5 \text{ cfm } * (\# \text{ bedrooms} + 1)] + [.01 \times \text{Sq. Ft.}]$ 

2,000 sq. ft., 3 Bedroom Home Example:

$$[7.5 * (3+1)] + [.01 * 2,000] = [30 + 20] = 50 cfm$$

## Meeting WHMV Requirements



- WHMV Fan Efficiency
  - For an example home of 4 BR and 2500 SF in CZ5:
    - Qfan = 0.01\*Afloor + 7.5(Nbr + 1)
    - = 0.01\*(2500) + 7.5\*(5) = 63 cfm

CZ 1-2	CZ 3, 4 (except Marine)	CZ 4 Marine, 5-8
2.8 cfm/W	2.8 cfm/W	1.2 cfm/W
No heat exchange	No heat exchange	HX with 60% SRE

• 63 cfm / (1.2 cfm/W) = 53 Watts BALANCED w/ 60% SRE

# Dilution: Whole-House Ventilation Exhaust-Only Ventilation









# Dilution: Whole-House Ventilation Supply-Only Ventilation





## Dilution: Whole-House Ventilation Balanced Ventilation





**ERV or HRV** 

# Dilution: Whole-House Ventilation Low-Cost Balanced Ventilation







#### **Simple Thru-Wall ERV**

- 90+% Heat Recovery
- 20-30% Humidity Recovery
- 1.4 2.8 W for
   10/18/22 CFM



# Dilution: Whole-House Ventilation Ventilation Challenge: Persistence













- Kitchen:
  - 100 CFM Intermittent
  - 5 ACH Continuous

- Bathrooms:
  - 50 CFM Intermittent
  - 20 CFM Continuous





# Filtration: High-MERV HVAC Filter







#### 8 MERV Filter Minimum

#### Verifying Homes – Indoor airPLUS



- 1-page checklist
- Builder or Rater may verify
- Permissible methods:
  - Visual verification on site during construction
  - Reviewing photos taken during construction
  - Checking documentation
  - Equivalent methods as appropriate
- Sampling permitted per RESNET protocol




# Zero Energy Ready Home Training Zero Specifications Efficient Components

## Zero Energy Ready Home Spec







\* Target only



#### **ENERGY STAR:**

- Appliances
- Exhaust Fans
- Ceiling Fans
- Water Heating\*

#### **Efficient:**

- Lighting
- Hot Water
   Distribution
- Equipment\*





Components and MEL's are increasingly larger part of total energy use in low-Load homes (~50%).



## Zero Energy Ready Home requires:

- ENERGY STAR Certified Appliances:\*
   refrigerators, dishwashers, clothes washers
- ENERGY STAR Certified Fans\*: bathroom ventilation, ceiling fans
- ENERGY STAR Certified Lighting:
   Min. 80% of fixtures or lamps (CFL or LED)
- WaterSense Hot Water Distribution

<sup>\*</sup>Only where installed by builder



# Zero Energy Ready Home Target Home also specifies **ENERGY STAR Water Heating**:

Water Heater Type	Target Home Water Heater's Energy Factor	
Gas/Propane ≤ 55 gallons	EF = 0.67	
Gas/Propane > 55 gallons	EF = 0.77	
Electric Systems	EF = 2.0	
Heating Oil	EF = 0.60	



# Zero Energy Ready Home Target Home also specifies **High-Efficiency Space Conditioning**:

	Target Home Efficiency		
HVAC Equipment	Hot Climates (IECC Zones 1,2)	Mixed Climates (IECC Zones 3, 4 except Marine)	Cold Climates (IECC Zones 4 Marine, 5, 6, 7, 8)
AFUE	80%	90%	94%
SEER	18	15	13
HPSF	8.2	9	10
Geo Heat Pump	ENERGY STAR EER/COP		

#### Indoor Fixtures

- Plumbing Fixtures
- Appliances and Other Equipment

#### Distribution

- Service Pressure
- Metering (for Multi-Family Homes)
- Leak Prevention
- Hot Water Distribution

#### Outdoor

- Landscape Design
- Irrigation (if installed)



#### Efficient Hot Water Distribution



- "Must Have" for zero net-energy ready homes
- Based on EPA WaterSense Specifications:
  - No more than 0.5 gallons of water in any piping/manifold between the hot water source and any hot water fixture.
  - No more than 0.6 gallons of water shall be collected from the hot water fixture before hot water delivered.
  - Timer- and temperature-based recirculating systems shall not be used to meet the criteria.



Built for when water was free and energy was cheap!

## Copper L piping:

- 1" = 5.53 ounces/ft
- $\frac{3}{4}$ " = 3.22 ounces/ft
- $\frac{1}{2}$ " = 1.55 ounces/ft


Storepole Volume:

306tgallons

10' branch

**Waitid** Time: 1 – 1.5

nin-lieshowerhead




#### Hot Water Distribution Options



- Core Plumbing Layout (wet wall)
- Manifold System
- Demand Pumping System


## Core Plumbing Layout




#### Manifold Plumbing System




#### 10' Max





#### **Demand Pumping System**





#### Verifying Hot Water Distribution



#### 1. Initiate Operation:

Turn on any occupant-controlled or occupancy sensor-based recirculation systems, if present.

#### 2. Container Placement:

Locate bucket or flow measuring bag pre-marked for 0.6 gallons under the hot water fixture. Only need to test fixture with greatest stored volume of hot water.

## 3. Turn on Hot Water Over Digital Thermometer:

Record starting temperature.

#### 4. Final Measurement:

When water reaches 0.6 gallons in container, record temperature again. A minimum increase of 10° F is required to pass the test.



# Zero Energy Ready Home Training Zero Specifications

Zero Specifications


## **Solar Ready Construction**

## Zero Energy Ready Home Spec
















#### Average Daily Solar Radiation Per Month



## Screen for RERH Applicability



#### Renewable Energy Ready Checklists

- Determine applicability by zip code
- http://gisatnrel.nrel.gov/PVWatts\_Viewer/index.html
- In this Mid-Atlantic example, solar resources = 4.8 kWh/m²/day





Not required in areas lacking access to significant solar resources:

- Tree Shading
- Tall Buildings
- Available South Facing Roof



**Documentation** of the maximum allowable dead load and live load ratings of the existing roof (Rec DL.: 6 lbs./sq. ft.)

Conduit to run DC wire from roof to inverter


#### **Dedicated Area**

for installing inverter and balance of system


Conduit to run AC wire from inverter location to electric panel

#### **Circuit Breaker**


designated and/or installed for use by the PV system in the electric panel



#### Integrated Renewable Energy



PV Mounted on Roof




PV Integrated into Front or Rear Porch Roof Directly on Porch Framing



## **Benefits:**

- Cost
- Appearance
- Maintenance
- Daylighting



PV Integrated into Front or Rear Porch Roof Directly on Porch Framing

# Integrated Renewable Energy





# Integrated Renewable Energy



# Integrated Renewable Energy



# Verifying Homes – RERH



- RERH checklist for DOE ZERH Home
  - builder or rater may verify



# Zero Energy Ready Home Training Zero Specifications Summary

# Stepping up to ZERH Summary...




		Solar Ready	Solar Ready			
				Eff. Comps.& H <sub>2</sub> O Distrib.	Eff. Comps.& H <sub>2</sub> O Distrib.	
		EPA Indoor Air Package	EPA Indoor Air Package			
				Ducts in Condit. Space	Ducts in Condit. Space	
		HVAC QI with WHV	HVAC QI with WHV	HVAC QI with WHV	HVAC QI + HRV	
		Water Management	Water Management	Water Management	Water Management	
		Independent Verification	Independent Verification	Independent Verification	Independent Verification	
IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2009 Enclosure	IECC 2012 Enclosure	IECC 2012/15 Encl./ES Win.	Ultra-Efficient Enclosure	
HERS <b>85-90</b>	HERS <b>70-80</b>	HERS <b>65-75</b>	HERS <b>55-65</b>	HERS 48-55	HERS <b>35-45</b>	
IECC 2009	IECC 2012	ENERGY STAR v3	ENERGY STAR v3.1	ZERH	PHIUS+	



# Zero Energy Ready Home Training Zero Recognition

# Pent-up ZERH Demand



Saturday, June 16, 2012 WASHINGTON, DC 511,688 (8) Newspaper (D)

Model home shows off its

eco-friendly and features to buyers

BY V. DION HAYNES

"Becoming more environmentally friendly has been the focus of the country," Moran added. "We want to give people a vision of where we think home building will be in a few years."

Thus far, net-zero houses are a very tiny segment - perhaps as small as 1 percent - of the market.

Production of energy from solar panels, one of the largest components of the green-home movement, is growing. The amount of megawatts produced by home solar panels rose 104 percent in 2010, 109 percent in 2011 and is expected to increase 75 percent this year, according to Boston-based GTM Research, a consult-

"They didn't have this [model] when we purchased our home" three doors down the street in October, said Nickiea Youmans, who along with her husband, Linzy, walked into the back yard to check out the house. "We would have been very interested in this," she added.

65 2012 The Washington Post Co.

# ZERH Resources: Marketing



- Branding [Logos, Home Certificates, Labels]
- 'Tour of Zero'/National Campaign
- Sales Training Webinar
- Customizable Point-of-Sale Fact Sheet
- Customizable Homebuyer Brochures
- Customizable Homeowner Manual
- Building Science Translator Sales Tool (BASC)
- Drop-in DOE Messaging
- Trade-Partner Recognition Form
- Leading Builder Round-Table Meetings

# ZERH Resources: Recognition



- DOE 'Tour of Zero'
- DOE Housing Innovation Awards
- Press Release Templates for Award Winners
- Web Site Locator Tool
- Home Builder Profiles



Nearly 1 in 3 consumers indicated they

# do not trust


home building and real estate companies.

Source: The business of Trust – The Most Trusted Builders in America, Lifestory Research, January 2013





- Rater Prints
   Certificate
   directly from rating software
- Certificate Includes:
  - Rating Details
  - Graphic HERS Index
  - Optional Programs



### Recognition with ZERH 'Brand'





Independent Voice of Authority vs. "Trust me."



# **Links Buyers to Leading Edge Builders:**

- Contact Information
- Optional Commitments:









- # Labeled Homes
- Website link

For All Active Partners

DOE Zero Energy	y Ready Home Partner Locator
allows you to view the number o	s have become DOE Zero Energy Ready Home partners. The interactive map below f partners by state and organizational type. Search for partners by typing into the text box rs by state, organization type, or commitments.
Ready to Take the Zero I	Energy Ready Challenge?
Builders interested in learning m process.  Search Partners:	ore about DOE Zero Energy Ready Home can view the requirements or start the sign up
Search  Or Filter By: State:  All   Partner Type:  All	WA  OR  OR  OR  OR  OR  OR  OR  OR  OR  O

### Recognition with ZERH Locator

### DOE Zero Energy Ready Home: Results

### Back to Map


Name	Туре	HIA Winner	City	State	DOE ZERH Projects	Builders Challenge Homes					
100% Partners											
Palo Duro Homes, Inc.	Builder	2013, 2014, 2015	Farmington	NM	208	235					
Mandalay Homes	Builder	2013, 2014, 2015, 2016	Phoenix	AZ	183	0					
Thrive Home Builders	Builder	2013, 2014, 2015, 2016, 2016	Denver	со	169	0					
Mutual Housing California	Builder	2015	Sacramento	CA	62	0					
Habitat for Humanity So. Sarasota, Inc.	Builder	2014, 2015, 2016	Venice	FL	21	0					
Greenhill Contracting Inc.	Builder	2014, 2015, 2015, 2015, 2016, 2016	ESOPUS	NY	20	9					
Charles Thomas Homes	Builder	2015	Elkhorn	NE	18	0					
Amaris Homes, LLC	Builder	2015, 2016	Maplewood	MN	10	4					
TCLegendHomesLLC	Builder	2013, 2014, 2015, 2016, 2016, 2016, 2016, 2016	Bellingham	WA	9	0					

### Recognition with ZERH Locator



### DOE Zero Energy Ready Home: Partner Profile

### **Mandalay Homes**









Partner ID: 620
Organization Type: Builder

Main Contact: Dave Everson

Address: 2320 E BASELINE RD #148-605

PHOENIX, AZ 85042
Primary Phone Number: (602) 864-3800

Certified DOE Zero Energy Ready Homes

(2012 - Present):

**Certified Builders Challenge Homes** 

(2008 - 2012):

Website:

183

0


http://www.mandalayhomes.com

# Recognition with 'Brand'



# Recognition with 'Brands'





### Recognition with Value Message





### **Lives Better**

### HEALTHFUL ENVIRONMENT

Every DOE Zero Energy Ready Home has a comprehensive package of measures to minimize dangerous pollutants, provide continuous fresh air, and effectively filter the air you breathe.

### COMFORT PLUS

Superior insulation, windows, air sealing and space conditioning systems included in every DOE Zero Energy Ready Home surround you with even temperatures, low-humidity, and quiet in every room on every floor.

KEY DOE Zero Energy Ready Home ENERGY STAR Certified Home Existing Home



### **Works Better**

### ADVANCED TECHNOLOGY

Every DOE Zero Energy Ready Home begins with solid building science specified by ENERGY STAR for Homes, and then adds advanced technologies and practices from DOE's worldclass research program, Building America.

### **ULTRA EFFICIENT**

Compared to a typical home, an ultra efficient Zero Energy Ready Home is inexpensive to own. In fact, every DOE Zero Energy Ready Home is so energy efficient, a small solar electric system can easily offset most, or all. of your annual energy consumption. We call this Zero Net-Energy Ready.



### **Lasts Better**

### QUALITY BUILT

Advanced construction practices and technologies are specified for every DOE Zero Energy Ready Home. Then they are enforced by Independent verifiers with detailed checklists and prescribed diagnostics.

The advanced levels of energy savings, comfort, health, durability, quality and future performance in every DOE Zero Energy Ready Home provide value that will stand the test of time, and will meet and exceed forthcoming code requirements.

LEARN MORE AT: buildings.energy.gov/zero

### The Future of Housing—Today

Only a select group of the top builders in the country meet the extraordinary levels of excellence and quality specified by U.S. Department of Energy guidelines.



LEARN MORE AT: buildings.energy.gov/zero



303-231-4567 ThriveHomeBuilders@net.com 123 Main Street, Denver, CO 34567



HEALTHFUL ENVIRONMENT

ADVANCED TECHNOLOGY

COMFORT PLUS

ULTRA EFFICIENT

QUALITY BUILT

DURABILITY

### A Symbol of Excellence



KEY DOE Zero Energy Ready Home ■ ENERGY STAR Certifled Home Existing Home

This label indicates relative performance of this DOE Zero Energy Ready Home to existing homes (built between 1990 and 2010) and ENERGY STAR Certifled Homes. Actual performance may vary.



Front Cover

Inside Spread

Flap

**Back Cover** 

# Recognition with Power Words



# Recognition with Awards







### Recognition with Awards



Home | About | Your Team | Accolades | Testimonials | Videos | Login

Find Your Home Design Your Home Browse Our Galleries

Latest News

Contact Us



Why Cobblestone Channel | Innovation Channel | Cobblestone Care Channel

# Michigan's Most Respected Builder

### CONTACTUS



Sales: (989) 692-0210

Office: (989) 692-0140

Fax: (989) 692-0142

### Design Studio Address:

5474 Garfield Rd Suite 2 Saginaw, MI 48603 MAP

### Mailing Address:

P.O. Box 604 Freeland, MI 48623 EMAIL



# Recognition with Tour of Zero



### Recognition with Tour of Zero





# Recognition with Tour of Zero



### **National Campaign:**

### **Call to Action:**

Inspire American homebuyers and home owners to visit the future of housing available today with DOE Zero Energy Ready Certified Homes.

### **Campaign Partners:**

- Manufacturers
- Associations
- NGO's
- Financial Institutions





### **Drop-In Messaging**

As a registered DOE Zero Energy Ready Home partner, enjoy access to the following pre-approved messages for insertion into your promotional materials. Simply insert your company name and use the message as it appears below.

- According to the U.S. Department of Energy, <Partner Name> is in a select group of top builders in the nation who have certified one or more homes that meet or exceed Zero Energy Ready Home guidelines for excellence in performance and energy efficiency.
- As a committed DOE partner who provides certified Zero Energy Ready Homes, <Partner name> is in the top one percent of builders in the country meeting the extraordinary levels of excellence in energy and performance specified in the national program requirements.
- . As a Zero Energy Ready Home Partner, < Partner Name > offers high performance homes that are so energy efficient, all or most of their annual energy consumption can be offset with renewable energy.
- <Partner name> builds homes certified to rigorous DOE Zero Energy Ready Home National Guidelines that are at least 40%-50% more energy efficient than a typical new home.
- Healthful environment:

According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home has a comprehensive package of measures to help minimize dangerous pollutants, provide continuous fresh air, and effectively filter the air you breathe.

Comfort Plus:

According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home features high-efficiency insulation, windows, air sealing and space conditioning systems that help surround you with even temperatures, low-humidity, and quiet in every room on every floor.

Advanced Technology:

According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home features advanced technologies and practices recommended by leading housing experts from DOE's world-class research program, Building America.

### Ultra efficient:

According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home is so energy efficient a small solar electric system can easily offset most, or all, of its annual energy consumption. This is why it is called as Zero Energy Ready Home.

### Quality Built:

According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home features high-efficiency appliances and equipment that are often associated with better quality construction. In addition, overall quality is enhanced with rigorous inspections, diagnostics, and checklists enforced by independent verifiers.

- Durability:
  - According to the U.S. Department of Energy (DOE), every certified Zero Energy Ready Home features advanced levels of energy savings, comfort, health, durability, quality and future performance that can be expected to stand the test of time and help enhance future value.
- Samuel Rashkin, Chief Architect for DOE Building Technologies Office, said "Zero Energy Ready Homes like those constructed by <Partner Name> are the home of the future because they live, work, and last better with incredibly low or no energy costs. And what's exciting for American homebuyers, they are available today thanks to leading builders across the country."
- "Housing Innovation Award winners such as <Partner Name who has won HIA> are leading a major housing industry transformation to zero energy ready homes. This level of performance is the home of the future because it improves the way Americans live by substantially reducing or eliminating utility bills, ensuring engineered comfort way beyond traditional homes, protecting health with a comprehensive package of indoor air quality measures, and helping maximize the largest investment of a lifetime," said Sam Rashkin, Chief Architect at the U.S. Department of Energy's Building Technologies Office.

# Recognition with 'Voice of Authority' ENERGY





According to DOE, Zero Energy Ready Homes are the homes of the future because they meet or exceed next generation energy codes and include substantial innovations and best practices recommended by leading housing experts working with the DOE Building America program. Homebuyers can buy these visionary homes today, including Treseder, which is available for sale now with the model home opening on August 1, 2015. By meeting or exceeding DOE requirements, these

## Recognition with 'Voice of Authority'



"Zero Energy Ready Homes are the future of U.S. housing, and innovators like New Town Builders are leading the way for the entire industry. Zero Energy Ready Homes can provide a vastly superior homeowner experience at a lower ownership cost – an experience all Americans should want in their next home."

Sam Rashkin, Chief Architect for U.S. Department of Energy Building Technologies Office

# Recognition After-Sale








BROUGHT TO YOU BY ——

### **Thrive Home Builders**

303-231-4567 ThriveHomeBuilders@net.com 123 Main Street, Denver, CO 34567



# Recognition After-Sale



### **High-Performance Thermal Enclosure**



The roof, walls, windows, doors, and foundation combine to form your home's enclosure.

You've got one chance to get it right during construction before it's locked in for the next few hundred years. That's why your home includes the leading expert recommendations for advanced thermal protection that provide significant utility bill savings along with enhanced comfort and durability.



### High-Performance Windows

use advanced technology to keep heat in during the winter and out during the summer while brightening your living space all year long.



### High-Performance Insulation

provides a complete thermal blanket that snugly surrounds your home in comfort and quiet.



### **Comprehensive Draft Protection**

is like wrapping your house in money with much lower heating and cooling bills while also blocking annoying dust, pollen, pests, noise, and moisture.



Any time work is being done on your home that involves wall penetrations or workers in your attic, make sure the contractor is required to maintain the insulation levels and air-tight construction.



# ZERH Partner Registration



### Review

- Technical Guidelines
- Partnership Agreement Terms

# Register

Electronically Sign Agreement

# Choose Optional Commitments:



100% of homes meet DOE Zero Energy Ready Home Guidelines



Homes meet EPA's WaterSense Guidelines



Homes meet IBHS's Fortified Home Guidelines



Meet DOE ZERH Home Quality Management Program

## ZERH Partner Responsibilities



- Take Orientation Training
   after registering and renew training every year
- Provide Certificate
   for DOE Zero Energy Ready Home to each home owner
- Adhere to Brand Identity Guidelines
   for proper use of the DOE Zero Energy Ready Home name and logo
- Build/Verify at Least One Home/Year to maintain active partnership

To view the full Agreement terms and disclaimers, visit: <a href="http://www1.eere.energy.gov/buildings/zero/">http://www1.eere.energy.gov/buildings/zero/</a>

- Update Company Information;
- Add, Delete, and Edit Contacts;
- Add/Update Your Logo;
- Add Commitments; and
- Access Key Tools and Resources







# **Thank You**



#### For More Information:

www.buildings.energy.gov/zero/

#### **Email Contact:**

zero@newportpartnersllc.com



# Zero Energy Ready Home Training

# **Alternate Slides**

# Performance Path Example CZ2 Prototype - 4 BR, 3500 SF



Specification	Target Home Spec	Design Home
Mandatory Items: ducts in conditioned space; 2012 IECC insulation; etc.		Meets all mandatory items; uses total UA to meet insulation reqmnt.
Windows	U=0.40; SHGC=0.25	U=0.32; SHGC=0.24
Infiltration	3 ACH50	2.5 ACH50
Duct Leakage	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	Total leakage ≤ 280 CFM25 Leakage to outdoors ≤ 140 CFM25
Furnace AFUE	80	92
A/C SEER	18	16
Whole-House Mech. Vent.	75 cfm; 1.4 cfm/W;	75 cfm; 5.0 cfm/W
Water Heater	ENERGY STAR	Gas storage 0.67 EF
Target Home HERS Index	55; ( <b>52 with SAF</b> )	
HERS Index – Design Home		52 – COMPLIES!

# Performance Path Example CZ4 Prototype - 4 BR, 2400 SF



Specification	Target Home Spec	Design Home
AGW Insulation	R20 or R13+5	R21
Attic Insulation	R49 (U=0.026)	R50
Basement Walls	R10/13	R10
Windows	U=0.30; SHGC=0.27	U=0.30; SHGC=0.27
Infiltration	2.5 ACH50	3.0 ACH50
Ducts	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	Total leakage 288 CFM25 Leakage to outdoors 140 CFM25
Furnace AFUE	90	90
A/C SEER	15	15
Whole-House Mech. Vent.	77 cfm; 1.4cfm/W no heat exchange;	77 cfm; 8.0 cfm/W exhaust-only
Water Heater	ENERGY STAR	Gas storage 0.67 EF
HERS Index	52	52 COMPLIES!

# Performance Path Example CZ5 Prototype - 4 BR, 2400 SF



Specification	Target Home Spec	Design Home
AGW Insulation	R20 or R13+5	R20
Attic Insulation	R49 (U=0.026)	R50
Basement Walls	R15/19	R10
Windows	U=0.27; SHGC=0.40	U=0.32; SHGC=0.30
Infiltration	2.0 ACH50	2.0 ACH50
Ducts	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	Total leakage 288 CFM25 In Conditioned Space w/ ½ ACH50 (Req.'d by ENERGY STAR) – Exempt
Furnace AFUE	94	90
A/C SEER	13	13
Whole-House Mech. Vent.	77 cfm; 1.2cfm/W balanced;	77 cfm; 8.0 cfm/W exhaust-only
Water Heater	ENERGY STAR	Gas storage 0.67 EF
HERS Index	52	52 COMPLIES!

# Performance Path Example CZ5 Prototype - 4 BR, 2400 SF



Specification	Target Home Spec	Design Home
AGW Insulation	R20 or R13+5	R20
Attic Insulation	R49 (U=0.026)	R50
Basement Walls	R15/19	R10
Windows	U=0.27; SHGC=0.40	U=0.32; SHGC=0.30
Infiltration	2.0 ACH50	2.0 ACH50
Ducts	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	Total leakage 288 CFM25 In Conditioned Space w/ ½ ACH50 (Req.'d by ENERGY STAR) – Exempt
Furnace AFUE	94	90
A/C SEER	13	13
Whole-House Mech. Vent.	77 cfm; 1.2cfm/W balanced;	77 cfm; 8.0 cfm/W exhaust-only
Water Heater	ENERGY STAR	Gas storage 0.67 EF
HERS Index	52	52 COMPLIES!

# Performance Path Example CZ6 Prototype - 4 BR, 2400 SF



Specification	Target Home Spec	Design Home
AGW Insulation	R20+5 or R13+10	21+5
Attic Insulation	R49 (U=0.026)	R50
Basement Walls	R15/19	R10
Windows	U=0.27; SHGC=0.40	U=0.32; SHGC=0.30
Infiltration	2.0 ACH50	2.5 ACH50
Ducts	Total ≤ 8 CFM25 per 100 SF of CFA; Leakage to outdoors ≤ 4 CFM25 per 100 SF of CFA	In Conditioned Space Total leakage 316 CFM25 Outdoors 120 CFM25
Furnace AFUE	94	95
A/C SEER	13	13
Whole-House Mech. Vent.	77 cfm; 1.2cfm/W balanced;	77 cfm; 8.0 cfm/W exhaust-only
Water Heater	ENERGY STAR	Gas storage 0.67 EF
HERS Index	46	46 COMPLIES!



# Climate Zones 1 and 2:

Walls: R-13 (R-13+5 recommended by CH)

Ceiling: R-30 (CZ1); R-38 (CZ2)

Floor: R-13 (R-19 recommended by CH)

Basement: R-0

Crawl Space: R-0

Slab: R-0



# **Climate Zone 1:**

Walls: R-13 (R-13+5 recommended by CH)

Ceiling: R-30

Floor: R-13 (R-19 recommended by CH)

Basement: R-0

Crawl Space: R-0

Slab: R-0



# **Climate Zone 2:**

Walls: R-13 (R-13+5 recommended by CH)

Ceiling: R-38

Floor: R-13 (R-19 recommended by CH)

Basement: R-0

Crawl Space: R-0

Slab: R-0



# **Climate Zone 3:**

Walls: R-20 or R-13+5

Ceiling: R-38

Floor: R-19

Basement: R-5/13

Crawl Space: R-5/13

Slab: R-0 (R-5 recommended by CH)



# **Climate Zone 2:**

**Walls**: R-13

(R-13+5 Recommended)

Ceiling: R-38

Floor: R-13

**Basement:** R-0

**Crawl Space:** R-0

Slab: R-0

# **Climate Zone 3:**

**Walls:** R-20 or R-13+5

(R-13+5 Recommended)

Ceiling: R-38

Floor: R-19

Basement: R-5/13

Crawl Space: R-5/13

**Slab**: R-0

(R-5 Recommended)



# **Climate Zone 4:**

Walls: R-20 or R-13+5

Ceiling: R-49

Floor: R-19

Basement: R-10/13

Crawl Space: R-10/13

Slab: R-10 for 2 ft. depth

	CZ 2	CZ 4
Walls	R-13 (rec. R13+5)	R-20 or R-13+5 (rec. R-13+5)
Ceiling	R-38	R-49
Floor	R-13	R-19
Basement	R-0	R-10/13
Crawl Space	R-0	R-10-13
Slab	R-0 (rec. R-5 slab edge)	R-10, 2' Deep



# **Climate Zone 5:**

Walls: R-20 or R-13+5

Ceiling: R-49

Floor: R-30

Basement: R-15/19

Crawl Space: R-15/19

Slab: R-10 for 2 ft. depth



	CZ 2	CZ 3
Walls	R-13 (rec. R13+5)	R-20 or R-13+5 (rec. R-13+5)
Ceiling	R-38	
Floor	R-13	R-19
Basement	R-0	R-5/13
Crawl Space	R-0	R-5-13
Slab	R-0 (rec. R-5 slab edge)	



	CZ 4	CZ 5
Walls	R-20 o	r R-13+5
Ceiling	R	-49
Floor	R-19	R-30
Basement	R-10/13	R-15/19
Crawl Space	R-10/13	R-15-19
Slab	R-10 for 2' Deep	

	CZ 5 IECC 2012	CZ 5 IECC 2012 RI
Walls	R-20 or	R-13+5
Ceiling	R-49	R-38
Floor	R-30	
Basement	R-15/19	R-13/10
Crawl Space	R-15/19	R-13/10
Slab	R-10/2 ft. Deep	
Window	U-0.32	U-0.35



	CZ 5	CZ 6
Walls	R-20 or R-13+5	R-20+5 or R-13+10
Ceiling	R-49	
Floor	R-30	
Basement	R-15/19	
Crawl Space	R-15/19	
Slab	R-10/2' Deep	R-10/4' Deep



# **Climate Zone 6:**

Walls: R-20+5 or R-13+10

Ceiling: R-49

Floor: R-30

Basement: R-15/19

Crawl Space: R-15/19

Slab: R-10 for 4 ft. depth



# **Climate Zone 7:**

Walls: R-20+5 or R-13+10

Ceiling: R-49

Floor: R-38

Basement: R-15/19

Crawl Space: R-15/19

Slab: R-10 for 4 ft. depth



## Climate Zone 5:

Walls: R-20 or R-13+5

Ceiling: R-49

Floor: R-30

Basement: R-15/19

Crawl Space: R-15/19

Slab: R-10 for 2 ft. depth

# **Climate Zone 6:**

Walls: R-20+5 or R-13+10

Ceiling: R-49

Floor: R-30

Basement: R-15/19

Crawl Space: R-15/19

Slab: R-10 for 4 ft. depth



	Climate Zone 6	Climate Zone 7
Walls	R-20+5 or	r R-13+10
Ceiling	R-49	
Floor	R-30	R-38
Basement	R-15/19	
Crawl Space	R-15/19	
Slab	R-10/4' Deep	



Zone 6:

**Zone 7:** 

Walls: R-20+5 or R-13+10

R-20+5 or R-13+10

Ceiling: R-49

R-49

Floor: R-30

R-38

Basement: R-15/19

R-15/19

Crawl Space: R-15/19

R-15/19

Slab: R-10 for 4 ft. depth

R-10 for 4 ft. depth



	CZ 5	CZ 6
Walls	R-20 or R-13+5	R-20+5 or R-13+10
Ceiling	R-49	
Floor	R-30	
Basement	R-15/19	
Crawl Space	R-15/19	
Slab	R-10/2' Deep	R-10/4' Deep



# Ceiling, wall, floor, and slab insulation:

Exceed 2012 WA State Energy Code Levels [Tables 402.1.1 and 402.1.3]

## Wall U-Value:

 $\leq 0.043$ 

[e.g., R-21 wall insulation AND R-5 contin. foam]

## Prescriptive Requirements



	Climate Zone	Fenestration	Skylight U-Factor	Glazed Fenestration SHGC	Ceiling R-Value	Wood Frame Wall R-Value
	1	NR	0.75	0.25	30	13
	2	0.40	0.65	0.25	38	13
	3	0.35	0.55	0.25	38	20 or 13+5 <sup>h</sup>
	4 except Marine	0.35	0.55	0.40	49	20 or 13+5 <sup>h</sup>
	5 & Marine 4	0.32	0.55	NR	49	20 or 13+5 <sup>h</sup>
	6	0.32	0.55	NR	49	20+5 or 13+10 <sup>h</sup>
	7 & 8	0.32	0.55	NR	49	20+5 or 13+10 <sup>h</sup>

## Prescriptive Requirements (cont.)



Climate Zone	Mass Wall R-Value <sup>i</sup>	Floor R- Value	Basement <sup>c</sup> Wall R-Value	Slab <sup>d</sup> R- Value, Depth	Crawl Space <sup>c</sup> Wall R- Value
1	3/4	13	0	0	0
2	4/6	13	0	0	0
3	8/13	19	5/13 <sup>f</sup>	0	5/13
4 except Marine	8/13	19	10 /13	10, 2 ft	10/13
5 & Marine 4	13/17	30 <sup>g</sup>	15/19	10, 2 ft	15/19
6	15/20	<b>30</b> <sup>g</sup>	15/19	10, 4 ft	15/19
7 & 8	19/21	38 <sup>g</sup>	15/19	10, 4 ft	15/19

## Equivalent U-Factors a



Climate Zone	Fenestration	Skylight U- Factor	Ceiling U- Factor	Frame Wall U-Factor
1	0.50	0.75	0.035	0.082
2	0.40	0.65	0.030	0.082
3	0.35	0.55	0.030	0.057
4 except Marine	0.35	0.55	0.026	0.057
o & Marine 4	0.32	0.55	0.026	0.057
6	0.32	0.55	0.026	0.048
7 & 8	0.32	0.55	0.026	0.048

A Non-fenestration U-factors shall be obtained from measurement, calculation, or an approved source.

## Equivalent U-Factors (cont.)




Climate Zone	Mass Wall U-Factor <sup>b</sup>	Floor U- Factor	Basement Wall U-Factor	Crawl Space Wall U-Factor
1	0.197	0.064	0.360	0.477
2	0.165	0.064	0.360	0.477
3	0.098	0.047	0 091°	0.136
4 except Marine	0.098	0.047	0.059	0.065
5 & Marine 4	0.082	0.033	0.050	0.055
6	0.060	0.033	0.050	0.055
7 & 8	0.057	0.028	0.050	0.055

<sup>&</sup>lt;sup>b</sup> When more than half of insulation is on interior, following maximum U-factors apply: CZ1-0.17, CZ2 – 0.14, CZ3 – 0.12, CZ4 (except Marine) – 0.087, CZ5 CZ4 Marine – 0.065, CZ6 -8 – 0.057.

#### **ENERGY STAR for Homes v3.1**




State	Applicable to Homes with the Following Permit Date		
MA	On or after 01/01/2015		
DC, IL, MD, RI	On or after 04/01/2015 (07/01/2015 for some counties).		
IA	On or after 06/01/2015		
DE	On or after 12/01/2015		
MT, OR, WA	On or after 01/01/2016		
MN	On or after 04/01/2016		
NV	On or after 07/01/2016		
NJ	On or after 04/01/2017		
TX	On or after 10/01/2017		






























HOME

#### "WHEN I SAW MY FIRST BILL AND I COMPARED IT TO MY LAST HOME'S BILL, I WAS SO IMPRESSED."

#### **Mandalay Homes**

Gordon Estates Phoenix, AZ mandalayhomes.com

"We love our home. We have enjoyed being here so much ... When I saw my first bill and I compared it to my last home's bill, I was so impressed. This is such a wonderful home."

- Mandalay homeownei







Read more.

#### ENERGY Energy Efficiency & Renewable Energy

DOE ZERO ENERGY READY HOME™ CASE STUDY

#### Mandalay Homes

Phoenix, AZ

#### **BUILDER PROFILE**

Mandalay Homes
Builder: Dave Everson
Phoenix, AZ, 602-864-3800
info@mandalayhomes.com

#### FEATURED HOME/DEVELOPMENT:

#### Project Data:

- Name: Gordon Estates
- Location: Phoenix, AZ
   Lavout: 4 bedrooms, 2.5 baths, 1 floor
- Conditioned Space: 1700 ft²
- Completion: June 2013
   Climate Zone: 4
- Category: Affordable

#### Performance Data:

- HERS Index without solar PV: 58
   HERS Index with solar PV: 38
- Projected annual utility costs: without solar \$1,179; with solar \$905
- Projected annual energy cost savings (compared to a home built to the 2006 IECC): without solar \$583; with solar \$857
- Annual energy savings: with solar 10,135 kWhs or 40.1 MMBtus; without solar 8,848 kWhs or 30.2 MMBtus

When builder Dave Everson, owner of Mandalay Homes, first heard about the U.S. Department of Energy's Zero Energy Ready Home program, he was skeptical. The production home builder was fecusing much of his time on affordable housing renovations for the City of Phoenix. The builder was already at better-than-code construction; he wondered how seeking even higher performance might impact the affordability of his homes.

**BUILDING TECHNOLOGIES OFFICE** 

But when the City of Phoenix awarded him the contract to build 14 new homes at Gordon Estates, a foreclosed subdivision of mostly empty lots, they stipulated that the homes should be a showcase for energy efficiency. When the previous builder foreclosed with only 6 of the 20 lots built, the property reverted to the city, which used federal Neighborhood Stabilization Program funds to sponsor the new construction there and in other Phoenix neighborhoods. The city recommended that Mandalay attain the National Green Building Standard (ICC 700) certification. Everson worked with green building consultant Philip Beere of G Street, who suggested the builder also pursue the EPA WaterSense and Indoor airPLUS certifications. Beere also introduced Everson to the DOE Zero Energy Ready Home program and suggested Everson use the HERS index as a design tool to pursue DOE Zero Energy Ready Home certification. Since the DOE program encompasses Indoor airPLUS and encourages WaterSense, DOE Zero Energy Ready Home certification was the next logical step.


Everson was taken with the idea of cutting his homes' HERS scores. "Everson really embraced the HERS index as a design tool. It became a challenge—how low can we go?" said Beere, who worked with Everson to bring his green homes to market. G Street provided third-party certification management, marketing tools, homeowner education, and design guidance. Everson had been following ENERGY STAR Version 2.0 for air sealing before Gordon Estates and analysis of some of his previous market-rate homes showed he had been achieving HERS scores in the




The U.S. Department of Energy Invites home builders across the country to meet the extraordinary levels of excellence and quality specified in DOE's Zero Energy Ready Home program (formerly known as Challenge Home). Every DOE Zero Energy Ready Home starts with ENERGY STAR for Homes Version 3 for an energy-efficient home built on a solid foundation of building science research. Advanced technologies are designed in to give you superior construction, durability, and comfort; healthy indoor air, high-performance HVAC, lighting, and appliances; and solar-ready components for low or no utility bills in a quality home that will last for generations to come.











Building **America:** Best Practices Research

DOE ZERH: Best Practices Label

**ENERGY STAR:** Above Code Label

**IECC** Code: Mandates

**Existing Home Upgrades**